

OIL INDIA LIMITED
(A Government of India Enterprise)
P.O. Duliajan, Pin – 786602
Dist-Dibrugarh, Assam

CORRIGENDUM

Amendment No. 01 Dated 16.03.2020
to Tender No. SDG3641P20/06 for SUPPLY, INSTALLATION &
COMMISSIONING OF CHEMICAL INJECTION SYSTEM

1.0 This Amendment No. 01 dated 16.03.2020 to Tender No. SDG3641P20/06 is issued to amend the following technical specifications of NIT item no 10 point D under item description instead of existing:

ITEM NO. / MAT CODE	EXISTING TENDER SPECIFICATION	AMENDED TENDER SPECIFICATION (marked as green colour)
10 (D) (99092009)	<p>Wellhead Adapter Spool (Qty-01 no.): Wellhead Adapter Spool, for downhole chemical dosing system, conforming to API 6A standard, as per drawing no OIL/PDNO/P&D/020/A-1/1 with the following specification:</p> <p>a) Materials : Minimum API 60 K, PSL1, U, AA, PR1, Cast/Forged Alloy steel.</p> <p>b) Top connection: Flanged, 3 1/8" x 5000 psi WP, RX 35 ring grooved, with internal 2 7/8" OD EUE API 8 TPI RD Tubing Thread for pick up.</p> <p>c) Bottom connection: Flanged, 7 1/16" x 5000 psi WP, RX 46 ring grooved, with internal 2 7/8" OD EUE 8 TPI RD Tubing Thread for hanging tubing (4000 m X 6.5 ppf).</p> <p>d) Minimum bore : 2.347" (Drift diameter).</p> <p>e) Chemical Injection port : Suitable provision for installing 3/8" control line for chemical injection system, with 1/2" port and 1/2" NPT thread at top & bottom.</p> <p>f) Accessories : The following accessories shall be provided along with the spool:</p> <p>i) Ring joint gasket, RX 35 - 01 no</p>	<p>Wellhead Adapter Spool (Qty-01 no.): Wellhead Adapter Spool, for downhole chemical dosing system, conforming to API 6A standard, as per drawing no OIL/PDNO/P&D/020/A-1/1 with the following specification:</p> <p>a) Materials : Minimum API 60 K, PSL1, U, AA, PR1, Cast/Forged Alloy steel.</p> <p>b) Top connection: Flanged, 2.9/16" x 5000 psi WP, RX 27 ring grooved, with internal 2 7/8" OD EUE API 8 TPI RD Tubing Thread for pick up.</p> <p>c) Bottom connection: Flanged, 7 1/16" x 5000 psi WP, RX 46 ring grooved, with internal 2 7/8" OD EUE 8 TPI RD Tubing Thread for hanging tubing (4000 m X 6.5 ppf).</p> <p>d) Minimum bore : 2.347" (Drift diameter).</p> <p>e) Chemical Injection port : Suitable provision for installing 3/8" control line for chemical injection system, with 1/2" port and 1/2" NPT thread at top & bottom.</p> <p>f) Accessories : The following accessories shall be provided along with the spool:</p>

	<p>for each spool. ii) Ring joint gasket, RX 46 - 01 no for each spool. iii) Studs & nuts, 1 1/8" x 6 1/4" - 08 sets for each spool. iv) Studs & nuts, 1.3/8" x 11 1/4" - 12 sets for each spool. DRAWING NO. : OIL/PDNO/P&D/020/A-1/1 ANNEXURE 8</p>	<p>i) Ring joint gasket, RX 27 - 01 no for each spool. ii) Ring joint gasket, RX 46 - 01 no for each spool. iii) Studs & nuts, 1" x 5.3/8" - 08 sets for each spool. iv) Studs & nuts, 1.3/8" x 7.48" - 12 sets for each spool. DRAWING NO. : OIL/PDNO/P&D/020/A-1/1 ANNEXURE 8</p>
--	---	---

2.0 All other Terms & Conditions of the Bid Document remain unaltered.

sd/-
Kumar Abhimanyu
Materials Manager (FD)
For GM-Materials
For Resident Chief Executive