

OIL INDIA LIMITED
(A Government of India Enterprise)
Rajasthan Project
Jodhpur, Rajasthan

CORRIGENDUM

Amendment No. 1 Dated 29.08.2019
To Tender No. SJG2139P20

This Amendment No. 1 dated 29.08.2019 to **Tender No. SJG2139P20 for 9.5/8" 13 CR Casing & Accessories** is issued as under:

- A. The technical specifications of item no. 10 (Material code: 01023750) is to be read as under in lieu of the existing:

Sl. No.	Material Code	Material Description
10	01023750	<p>CASING, Grade: L-80, Type:13 CR (API specification), CHROMIUM STAINLESS STEEL, SCREWED & COUPLED, CONFORMING TO API STANDARD 5CT GROUP 2, WITH API MONOGRAM ON EACH JOINT, IN RANGE-III LENGTH (MAX. LENGTH NOT TO EXCEED 12.2 MTRS). EACH JOINT FITTED WITH PRESSED STEEL OR ELASTOMER-CUM-METALLIC (COMPOSITE) THREAD PROTECTORS AT BOTH PIN AND BOX ENDS.</p> <p>244.475 mm (9.5/8") OD, 70 kg/mtr. (47PPF) nominal weight, Grade 13CR-80 with Premium thread. PREMIUM THREADS: ATLAS BRADFORD TC-II, JFE Fox & JFE Bear, TENARIS HYDRIL 563/3SB, VAM TOP, Hunting Seal Lock XD, Baosteel BGT2 brand gas tight premium connections with metal to metal seal and tested as per Cal IV requirements (version 2011 or later) for this OD.</p> <p>Negative load flank hooked-style thread form with Engineered thread compound relief groove to prevent dope entrapment.</p> <p>Tensile Efficiency: 100% Compressive Efficiency: 100% Maximum Bend: 38.1 Deg./100 feet Minimum Yield: 70,200 Ft*1bf</p>

All other Terms & Conditions of the tender remain unchanged.

Sd-
(B. Mody)
Manager Materials (M&C)