

OIL INDIA LIMITED
 (A Govt. of India Enterprise)
 P.O. Duliajan-786602, Assam
 Fax No. 91-374-2800533, E-mail:material@oilindia.in

Tender No. & Date : SSG4005P17/01 03.03.2017

Tender Fee : INR 30,000.00 OR USD 500.00
 Bid Security Amount : INR 781,500.00 OR USD 11,600.00
 (or equivalent Amount in any currency)

Bidding Type : Single Stage Two Bid System

Bid Closing On : 26.04.2017 at 11:00 hrs. (IST)

Bid Opening On : 26.04.2017 at 14:00 hrs. (IST)

Performance Guarantee : Applicable @10% of order value

OIL INDIA LIMITED invites Global tenders for items detailed below:

Item No./ Mat. Code	Material Description	Quantity	UOM
<u>10</u> 01010380	CASING - API 5.1/2" Premium Casing (Grades: N 80) Casing, API Seamless Steel, Premium Threaded & Coupled, shall conform to API 5CT (Latest Edition), with API Monogram, in Range-3 length but maximum length of each joint shall be restricted to 12.19 M (40 Ft.), fitted with pressed steel or Elastomer-cum- metallic (composite) thread protector on both ends: Size: 5.1/2"(139.70mm) OD Weight: 20lbs/ft.(29.76 kg/m) Group: 1 Grade: N-80 Type: Q Connection: Premium Threaded (BOX x PIN) Drift Diameter: Standard Coupling: Regular Colour Code: Red & Bright Green for Grade-N80, Type- Q in Conformance with API Spec.5CT. Production Specification Level: PSL-2.	20000	M
<u>20</u> 01010381	5.1/2" Premium Casing (Grade P-110) Casing, API Seamless Steel, Premium Threaded & Coupled, shall conform to API Spec. 5CT (Latest Edition), with API Monogram, in Range-3 length but maximum length of each joint shall be restricted to 12.19 M (40 Ft.), fitted with pressed steel or Elastomer-cum- metallic (composite) thread protector on both ends: Size: 5.1/2"(139.70mm) OD Weight: 20lbs/ft.(29.76 kg/m) Group: 3 Grade: P-110 Connection: Premium Threaded (BOX x PIN) Drift Diameter: Standard Coupling: Regular Colour Code: White for Grade P-110 in accordance with API Spec. 5CT.	3000	M

Tender No. & Date : SSG4005P17/01

03.03.2017

Item No./ Mat. Code	Material Description	Quantity	UOM
	Production Specification Level: PSL-2.		
60 01065387	<p>COUPLING FOR API CASING COUPLING FOR API CASING Casing Coupling, shall conform to API Spec. 5CT (Latest Edition), with API Monogram: Size: 5.1/2"(139.70mm) OD Weight: 20lbs/ft.(29.76 kg/m) Grade: P110 Group: 3 Connection: Premium Threaded (BOX x PIN) Colour Code: White for Grade P110 in Conformance with API Spec. 5CT Product Specification Level: PSL-2.</p>	10	NO
30 01112870	<p>A.P.I. CASING - SHORT JOINT (NIPPLE) A.P.I. CASING - SHORT JOINT (NIPPLE) Casing PUP joint, API Seamless Steel, Premium Threaded & Coupled, shall conform to API Spec. 5CT (Latest Edition), with API Monogram, fitted with pressed steel or Elastomer-cum- metallic (composite) thread protector on both ends: Size: 5.1/2"(139.70mm) OD Weight: 20lbs/ft.(29.76 kg/m) Group: 3 Grade: P110 Connection: Premium Threaded (BOX x PIN) Drift Diameter: Standard Coupling: Regular Colour Code: White for Grade P110 in Conformance with API Spec. 5CT Length: 79" (2000 mm) from box end to pin End with Tolerance of +/-6" (152mm). Product Specification Level: PSL-2.</p>	18	NO
40 01111997	<p>CROSS OVER CROSS OVER Casing Crossover joint, API Seamless Steel, Premium Threaded & Coupled, shall conform to API Spec. 5CT (Latest Edition), with API Monogram, fitted with pressed steel or Elastomer-cum- metallic (composite) thread protector on both ends: Size: 5.1/2"(139.70mm) OD Weight: 20lbs/ft.(29.76 kg/m) Group: 3 Grade: P110 Connection: Premium Threaded Box x Buttress Threaded Pin Drift Diameter: Standard Coupling: Regular Colour Code: White for Grade P110 in Conformance with API Spec. 5CT Length: 39" (1000 mm) from box end to pin End with Tolerance +/-6" (152mm) Product Specification Level: PSL-2.</p>	7	NO

Tender No. & Date : SSG4005P17/01

03.03.2017

Item No./ Mat. Code	Material Description	Quantity	UOM
50 01111998	<p>Casing Crossover joint, API Seamless Steel, Premium Threaded & Coupled, shall conform to API Spec. 5CT (Latest Edition), with API Monogram, fitted with pressed steel or Elastomer-cum- metallic (composite) thread protector on both ends:</p> <p>Size: 5.1/2" (139.70mm) OD Weight: 20lbs/ft (29.76 kg/m) Group: 3 Grade: P110</p> <p>Connection: Buttress Threaded Box x Premium Threaded Pin Drift Diameter: Standard Coupling: Regular Colour Code: White for Grade P110 in Conformance with API Spec. 5CT Length: 39" (1000 mm) from box end to pin End with Tolerance of +/-6" (152mm) Product Specification Level: PSL-2.</p>	7	NO

Note description for item no./nos. : 10, 20, 30, 40, 50, 60

- The colour coding (to assist weight identification at site) shown above to be applied to each length of casing near the centre of joint in the form of 2" wide band for each colour specified.
- Third party inspection is required.
- Elastomer-cum-metallic (composite) protector for pin and box and of casing should be extra strong closed end and of Drilltech make or it's suitable equivalent. The protector should be designed in such a way as to cover the full length of casing pin end threads as well as casing coupling threads. It should have steel shell and elastomer to reduce impact, stop corrosion, eliminate stripping and to keep the thread compound active.

SPECIAL NOTE:

1) Premium threaded end connection of the casing and accessories shall be from any one of the following specific types only. Any other premium connection or equivalent will not be acceptable.

- ATLAS BRADFORD TC-II
- HSC (High Sealed & Coupled).
- HUNTING SEAL LOCK-HC.
- KAWASAKI PREMIM FOX.
- NEW VAM OR VAM TOP.
- NIPPON STEEL NSCC-FGL.
- TENARIS HYDRILL WEDGE-563 or TENARIS HYDRIL 3SB or TENARIS HYDRIL MS.
- BAOSTEEL BGT2

2) The premium threads specified above shall be cut by licensor/Authorized licensee only. In case the casing Manufacturer/Processor/Threader is not the licensor of the quoted premium thread, they should submit the valid authorization/ license issued by Licensor in favour of Licensee for cutting the quoted premium threads.

3) Casing pipes (Mat. codes 01010380 & 01010381), pup Joints (Mat. code 01112870), cross over joints (Mat. codes 01111997 & 01111998) and couplings (Mat. code 01065387) shall be purchased from the same source/ manufacturer for compatibility. Bidder must quote for the full tendered quantity.

Tender No. & Date : SSG4005P17/01

03.03.2017

iv) Bidder must submit the technical catalogue/literature along with the offer indicating performance properties, recommended torque charts, operating/running guide and details of leak resistance of the quoted premium threaded connection.

Standard Notes: I) ALL ITEMS TO BE PROCURED FROM SAME SOURCE.
II) BIDDER TO QUOTE THEIR BEST DELIVERY PERIOD.

AA. STANDARD NOTES:

1) The tender is invited under SINGLE STAGE-TWO BID SYSTEM. The bidder has to submit both the "TECHNO-COMMERCIAL UNPRICED BID" and "PRICED BID" bid through electronic form in the OIL's e- Tender portal within the Bid Closing Date and Time stipulated in the e-Tender. The "TECHNO-COMMERCIAL UNPRICED BID" is to be submitted as per Scope of Work & Technical Specification of the tender and "PRICED BID" as per the Online Price Bid format.

2) In Technical Bid opening, only Technical Rfx will be opened. Therefore, the bidder should ensure that "TECHNO-COMMERCIAL UNPRICED BID" should contain details as mentioned in the technical specifications as well as BEC/ BRC and upload the same in the Technical RFX Response-> User -> Technical Bid. **No price should be given in above Technical Rfx otherwise the offer will be rejected.** Please go through the help document in details before uploading the document and ensure uploading of technical bid in the Technical RFX Response-> User -> Technical Bid only. The "PRICE BID" must contain the price schedule and the bidder's commercial terms and conditions. The prices of the items should be quoted in "Conditions Tab".

3) Bid should be valid for **minimum 120 days** from bid closing date, failing which offer shall be rejected.

4) The original bid security (Amount is mentioned above and also in Rfx Parameters of the tender in OIL's e-portal) should reach us before bid closing date and time of the technical bid. Bid without original Bid Security will be rejected. The bidders who are exempted from submitting the Bid Bond should attach documentary evidence in the Technical RFX Response-> User -> Technical Bid as per clause 9.8 of Section A General Terms and conditions for Global Tender (MM/GLOBAL/E-01/2005-July2012). The bid security shall be valid up to **26.11.2017**. Only payments through online mode or Submission of Bank Guarantee/LC will be acceptable. No DD/Cheques/Cashier Cheque or any other mode will be acceptable.

5) Performance Security @10% of order value is applicable against this tender. Please refer clause 10.0 of Section A of General Terms and conditions for Global Tender (MM/GLOBAL/E-01/2005 - July2012).

6) PRICED BIDS OF ONLY THOSE BIDDERS WILL BE OPENED WHOSE OFFERS ARE FOUND TECHNICALLY ACCEPTABLE. THE TECHNICALLY ACCEPTABLE BIDDERS WILL BE INFORMED BEFORE OPENING OF THE "PRICED BID".

7) Bidders to note that Govt. of India under Micro, Small and Medium Enterprises Development (MSMED) Act 2006, has proclaimed the Public Procurement Policy, 2012 with effect from 1st April, 2012 in respect of procurement of goods and services, produced and provided by micro and small enterprises, by its Ministries, Departments and Public Sector Undertakings for promotion and development of Micro and Small Enterprises. A new Clause on applicability of Public Procurement Policy for procurement of goods from Micro and Small Enterprises(MSE) in the tender is furnished vide Amendment to General Terms and Conditions for Global Tender (MM/GLOBAL/E-01/2005-JULY2012). Bidders are requested to take note of the same and to submit their offers accordingly.

Tender No. & Date : SSG4005P17/01

03.03.2017

8) To ascertain the substantial responsiveness of the bid OIL reserves the right to ask the bidder for clarification in respect of clauses covered under BRC also and such clarifications fulfilling the BRC clauses in toto must be received on or before the deadline given by the company, failing which the offer will be summarily rejected.

9) General terms and conditions of Global tender (document MM/GLOBAL/E-01/2005 - July 2012) is enclosed. Special attention to Bidders is drawn to the Section E of above document.

10) The Integrity Pact is applicable against this tender. Therefore, please attach the Integrity Pact document duly signed along with your quotation as per BRC. The name of the OIL's Independent External Monitor at present are as under:

1. SHRI RAJIV MATHUR, IPS (Retd.),
2. SHRI SATYANANDA MISHRA, IAS(Retd.)

The email ids are furnished in OIL's website, www.oil-india.com

11) OIL reserves right to go for Reverse Auction process or may finalize the tender without Reverse Auction, if required. However, the decision to conduct Reverse Auction or not will be conveyed to short-listed bidders prior to opening of price bid.

Special Terms & Conditions and salient features for Reverse Auction are furnished in Addendum- B. The Business Rules for Reverse Auction and Process Compliance Form are given in Addendum- B. Bidders are required to sign the Business Rules for Reverse Auction and Process Compliance Form and attach this document along with the technical bid.

Reverse Auction shall be conducted without loading Anti-Dumping duty (if applicable). However, after completion of the Reverse Auction, in case of Foreign bidders who have quoted goods originating from China and on whom the Anti-Dumping Duty is applicable as on date of Reverse Auction, Anti-Dumping duty so calculated as per the Notification shall be loaded on the final CIF Landed value quoted by those Foreign bidders (with Customs Duty as applicable on the Bid Closing Date of the Tender) in the Reverse Auction. The final evaluation of the offers will be done after loading Anti-Dumping duty on the prices obtained through Reverse Auction.

12) Price should be maintained in the "online price schedule" only. The price quoted in the "online price schedule" will only be considered.

13) Indigenous Bidder must indicate handling charge to the nearest Rail Head. If any Indigenous Bidder does not indicate the handling charge to the nearest rail head, their offer will be liable for rejection.

14) Tender fee Payment should be made only through online mode and no other instrument(Cash/DD/Cheques/Cashier Cheque, etc) will be acceptable.

BB. GENERAL NOTES FOR CASING

1.0 SPECIFICATION :

1.1 Casings must be manufactured as per API Spec. 5CT, latest edition and must bear API monogram. A copy of valid API Spec. 5CT certificate from the manufacturer shall be submitted along with the offer.

1.2 The Casings shall be brand new, unused, and of prime quality.

1.3 Casings shall be seamless , threaded and fitted with power tightened couplings as per API Spec. 5CT (latest edition).

1.4 Range : All casings shall be supplied in range III length. However, length of each joint should be restricted to 12.19 mtrs (40 ft.) max.

1.5 Coupling : Couplings shall be as specified in API Spec. 5CT (latest edition)and must be manufactured by API approved mills.

1.6 Coating : Coating shall be done as per API Spec. 5CT (latest edition) and adequately oiled to withstand sea voyage.

Tender No. & Date : SSG4005P17/01

03.03.2017

1.7 Pipe ends : Ends must be prepared as per relevant API specifications including clear triangle mark in case of Buttress thread. Suitable pressed steel / Elastomer-cum-metallic (Composite) thread protectors at both ends as specified in API 5CT (latest edition) shall be used to protect the ends.

Note : Elastomer-cum-Metallic (Composite) thread protectors for pin and box end of the casing should be extra strong, closed end & of Drilltech make or it's suitable equivalent. The protector should be designed in such a way that it covers the full length of casing threads as well as casing coupling threads. It should have steel shell and elastomer to reduce impact design, to stop corrosion, to eliminate stripping and to keep thread compound active.

1.8 The offer must contain detailed description of the materials giving details of size, weight/wall thickness, grade, length range, type of end, API Std., end protectors etc. Insufficient description will lead to rejection of the offer.

1.9 THE OFFER MUST CONTAIN THE VARIOUS PERFORMANCE PROPERTIES OF THE OFFERED PRODUCT VIZ. COLLAPSE RESISTANCE, INTERNAL YIELD PRESSURE, PIPE BODY YIELD STRENGTH & JOINT STRENGTH (THESE PROPERTIES SHOULD NOT BE LESS THAN THOSE STIPULATED BY API, BUL 5C2, LATEST EDITION IN ANY CASE). FAILURE TO COMPLY WITH THE ABOVE MAY LEAD TO REJECTION OF THE OFFER.

2.0 MILL INSPECTION, TESTING & CERTIFICATION:

2.1 The following tests and inspections shall be carried out as per API spec. 5CT (latest edition) and results thereof furnished to OIL along with the supply. Mill Test certificates are to be submitted to OIL in Original.

i) Testing of Chemical Composition.

ii) Testing of Mechanical Properties.

iii) Hydrostatic Tests.

iv) Dimensional testing (wall thickness, drift test, length, weight, determination and straightness).

v) Visual Inspection.

vi) Non-Destructive Inspection.

The manufacturer shall furnish a certificate of compliance stating that the material has been manufactured, sampled, tested and inspected in accordance with API Spec. 5CT (SR-15), latest edition. The above certificate should be submitted to OIL in Original.

2.2 End threading, gauging, thread inspection and certification shall be carried out as per API Std. 5B (latest edition).

3.0 IDENTIFICATION MARKING :

3.1 Marking is to be done on each joint strictly as per Appendix D of API Spec. 5CT.

3.2 Additionally, 'OIL' logo/mark and the purchase order number shall be die stamped or paint stenciled on each joint.

3.3 Colour coding: The colour coding shall be done as per API Spec. 5CT (latest edition). The colour band shall be 50.8 mm (2") wide and shall be encircling the pipe at a distance not greater than 2 ft. from the coupling or box with entire paint on the outside surface of coupling.

3.4 For Buttress threaded casings a 1" wide by 24" long longitudinal white paint stripe shall be placed adjacent to the triangle mark on the field end; additionally, a 1" wide by 4" long longitudinal white paint stripe shall be placed adjacent to the triangle mark on the mill end.

4.0 THIRD PARTY INSPECTION :

4.1 Inspection by an independent third party to cover the following shall be required against all casings.

(i) Material Identification.

(ii) Stage inspection at random visit basis during manufacturing.

(iii) Audit and endorsement of all chemical analysis and physical test reports.

(iv) Witness dimensional checks.

(v) Witness mechanical tests.

(vi) Witness NDT.

(vii) Witness hydrostatic tests

(viii) Visual inspection for imperfections.

Tender No. & Date : SSG4005P17/01

03.03.2017

- (ix) Longitudinal defect identification.
- (x) Transverse defect identification.
- (xi) Wall thickness measurement.
- (xii) Grade comparison.
- (xiii) End area defect identification.
- (xiv) Thread inspection.
- (xv) Check and verify length of each joint.
- (xvi) Issue of certificate.

Note : Proper Tally sheet (in Original) indicating length of each joint of Casing with heat number of the joint should be furnished to OIL. The Tally sheet should be duly signed & stamped by the Manufacturing Mill and will be endorsed (certified) by the third party inspection agency.

4.2 The third party inspection is to be carried out by an internationally reputed inspection Agency. Bidders must indicate the availability of such a Third Party Inspection Agency in their area furnishing following information.

- (i) Name of the Inspecting Agency (OIL's clearance has to be obtained prior to engagement except M/s. Lloyds, M/s Bureau Veritas, M/s. RITES, M/s. I.R.S., M/s. Tuboscope Vetco and M/s DNV.)
- (ii) All inclusive charges for Third Party Inspection per metre (to be indicated separately).

CC. ANTI-DUMPING DUTY

The Clause No. 3.0 in Section-'E' (Special Terms & Conditions for Tubulars) of General Terms & Conditions for Global Tender (MM-GLOBAL/E-01-2005-July 2012) on Anti-Dumping Duty stands deleted. In its place the following clauses on "Anti-Dumping Duty" shall be applicable-

1. The Anti-Dumping Duty, if any, shall be applicable as per the latest Govt. guideline and will be payable by the bidder. Bidders are requested to note the same and quote accordingly.
2. Anti-Dumping Duty shall be borne by the bidder as mentioned above. A categorical confirmation in this regard is required from the bidders along with their offer, otherwise their offer will not be considered for further evaluation.
3. All bidders must categorically mention the country of origin of the products offered by them in their offers. In the event categorical mention of country of origin of their offered products is not made in their offer, the offer will be summarily rejected.
4. In case of the indigenous bidders, they should note that OIL will not be liable to reimburse any amount on account of Anti-Dumping duty for the materials imported by them from People's Republic of China for execution of the contract and any Anti-Dumping Duty payable against import by them from People's Republic of China shall be to their account. Indigenous bidders are required to categorically confirm acceptance of the same in their Technical bids failing which offers will be liable for rejection.