

OIL INDIA LIMITED
(A Government of India Enterprise)
P.O. Duliajan, Pin – 786602
Dist.-Dibrugarh, Assam

AMENDMENT NO. 1 DATED 26.07.2018
TO TENDER NO SSG8305P19/03

This Amendment no. 1 dated 26.07.2018 to tender no. SSG8305P19/03 for **Procurement of Hydraulic Packer** is issued to change the detailed specification of item no. 10 as follows instead of the existing:

Sl. no & Material code	Existing Material Description	Modified Material Description
<p>10 05220120</p>	<p>ACCESSORIES FOR PACKER, HYDRAULIC SET, RETRIEVABLE Packer Hydraulic Set for 7"x 26-29 PPF "Packer, Hydraulic Set, complete with setting tools as per following requirement A) The packer shall be suitable for following duty conditions i) Casing Size : 177.8 mm (7") O.D. 38.77 - 43.25 Kg./m (26 -29 PPF) ii) Setting Depth: 1500 - 4500 m (5000 ft. - 14760 ft.) iii) Maximum working differential pressure: 351.5 Kg/Sq. Cm.(5,000 PSI) from both side. iv) Maximum Temperature at setting depth : 135 °C (275 °F) v) Service : Sweet B) The packer shall fulfil following dimensional parameters i) Maximum O.D of Packer.: 154.40 mm (6.080") ii) Minimum Bore of Mandrel: 60.30 mm (2.373") iii) End Connections : 73.03 mm (2.7/8") O.D. EUE 8RD API Threaded Box-up Pin-down C) The packer shall have the following features i) Minimum three elements pack off ii) Mechanically locked in iii) Bi directional / double grip slip system</p>	<p>ACCESSORIES FOR PACKER, HYDRAULIC SET, RETRIEVABLE Packer Hydraulic Set for 7"x 26-29 PPF "Packer, Hydraulic Set, complete with setting tools as per following requirement A) The packer shall be suitable for following duty conditions i) Casing Size : 177.8 mm (7") O.D. 38.77 - 43.25 Kg./m (26 -29 PPF) ii) Setting Depth: 1500 - 4500 m (5000 ft. - 14760 ft.) iii) Maximum working differential pressure: 351.5 Kg/Sq. Cm.(5,000 PSI) from both side. iv) Maximum Temperature at setting depth : 135 °C (275 °F) v) Service : Sweet B) The packer shall fulfil following dimensional parameters i) Maximum O.D of Packer.: 154.40 mm (6.080") ii) Minimum Bore of Mandrel: 60.30 mm (2.373") iii) End Connections : 73.03 mm (2.7/8") O.D. EUE 8RD API Threaded Box-up Pin-down C) The packer shall have the following features i) Minimum three elements pack off ii) Mechanically locked in iii) Bi directional / double grip slip system</p>

	iv) Retrievable type with straight pick-up release v) Adjustable shear release vi) Built-in equalizing system for reliable release D) The packer shall be provided with necessary hydraulic setting tool as detailed below i) Guide / Sub with 2 7/8" EUE 8RdAPI Threaded Box up & half mule shoe bottom ii) Shear out seat / plug iii) O rings iv) Setting Screws v) Ball	iv) Retrievable type with straight pick-up release v) Adjustable shear release vi) Built-in equalizing system for reliable release D) The packer shall be provided with necessary hydraulic setting tool as detailed below i) Guide / Sub with 2 7/8" EUE 8RdAPI Threaded Box up & half mule shoe bottom ii) Shear out seat / plug iii) O rings iv) Setting Screws v) Ball" Material Grade: L-80
--	--	--

All other terms and condition of the tender will remain unchanged.

sd-
Gitasree Sarmah
Sr. Purchase Officer (FS)
For DGM MATERIALS
For Resident Chief Executive