

**OIL INDIA LIMITED**  
(A Government of India Enterprise)  
P.O. Duliajan, Pin – 786602  
Dist-Dibrugarh, Assam

**AMENDMENT NO. 02 DATED 16.08.2019  
TO TENDER NO. SDG0913P19/08**

This **Amendment No.02** dated 16.08.2019 to **Tender No. SDG0913P19/08** is issued to extend the **Bid Closing / Bid Opening date** and amend the **Technical Specification** as under:

**A) BID CLOSING DATE:**

The Bid Closing / Bid Opening date is extended as under:

- i) Bid Closing Date & Time : **11.09.2019 (11.00 IST)**
- ii) Bid Opening Date & Time: **11.09.2019 (14.00 IST)**

**B) Technical Specification:**

Tender clause no	Tender Description	Amended Tender Description
AA: Clause A.) point a) Page 2 of 60 Overall dimension	Overall Dimension : The overall dimension of the Trailer mounted winch shall be approx. 1500mm (l) x 1000 mm (w) x 800 mm (h).	<b>Overall Dimension:</b> The overall dimension of the Trailer mounted winch shall be approx. <b>1850 mm (l) x 1350 mm (w) x 800 mm (h).</b>
AA: Clause A.) point c) II sub clause 2(ii) Page 3 of 60 Hydraulic oil reservoir	The inside of the tank shall be painted/coated with a sealer to prevent corrosion from condensed moisture. The sealer shall be chosen for compatibility with the fluid being used.	The inside of the tank shall be painted/coated with a sealer to prevent corrosion from condensed moisture. The sealer shall be chosen for compatibility with the fluid being used. <b>However, inside painting/coating is not required for Stainless steel Hydraulic tank.</b>
AA: Clause A.) point c) II sub clause 2(vii) Page 3 of 60 Hydraulic oil reservoir	Pump inlet and return lines must be well below the fluid level to prevent aeration and foam. Each hydraulic hose connections including drain plug shall be equipped with one isolating valve.	Pump inlet and return lines must be well below the fluid level to prevent aeration and foam. <b>Each Hydraulic hose connection from Hydraulic Reservoir including drain plug (i.e. pump suction and drain line) shall be equipped with isolating valve.</b>
AA: Clause A.) point III ) d) v) Page 3 of 60 winch drum	v) Line Capacity: 5500M (18000 ft) of 0.092" size slickline.	v) Line Capacity: <b>6173M (20000 ft)</b> of 0.092" size slickline
AA: Clause A.) point III ) i) iii) Page 5 of 60 Hay pulley assembly	iii) The line keeper is to be provided with adapter for line wiper.	<b>May be considered as deleted</b>
AA: Clause A.) point III ) j) Page 5 of 60 Slickline		<b>To be included</b> <b>J(v)</b> Make _____ of slickline:Danum/Techwire/Sandvik/DeAcer o
AA: Clause B) point a) Page 5 of 60 Trailer specifications	a.) The trailer is meant for mounting the winch equipment of overall dimension of approx. 1500 mm (l) x 1000 mm (w) x 800 mm (h) and weighing approx. 1000 kg having suitable skid.	The trailer is meant for mounting the winch equipment of overall dimension of approx. 1850 mm (l) x 1350 mm (w) x 800 mm (h) and weighing approx. 1000 kg having suitable skid.

<b>Tender clause no</b>	<b>Tender Description</b>	<b>Amended Tender Description</b>
AA: Clause B) point g) Page 5 of 60 Trailer specifications	g.) The front and the sideboards of the trailer shall be hinged type so that it can be opened & hanged downward at the time of winch operation.	<b>May be considered as deleted</b>
AA: Clause B) point j) sub clause b) Page 6 of 60 Trailer specifications (Material of construction)	b. The height of the side boards shall be 350 mm	The height of the side boards shall be approx. 450 mm.
AA: Clause B) point j) sub clause c) Page 6 of 60 Trailer specifications (Material of construction)	c. The canopy shall be lightweight for easy opening & closing by one or two persons. It shall be made of MS channel & 14-15 gauge aluminium sheets.	The canopy shall be light weight for easy opening & closing by one or two persons. It shall be made of MS channel & 17-18 gauge aluminium sheets.
AA: Clause B) point j) sub clause p) Page 6 of 60 Trailer specifications (Painting)	p.) Painting: One coat of primer and two coats of Imperial Crimson (DULUX GLOSS) paint for trailer shall be provided. Chassis paint for undercarriage shall be provided. Wheel rims shall be painted with black colour. All steel works shall be suitably painted	p.) Painting: One coat of primer and two coat of Imperial crimson / RAL 3002 paint for trailer shall be provided. Chassis paint for undercarriage shall be provided. Wheel rims shall be painted with black colour. All steel works shall be suitably painted
AA: Clause B) point e) Page 5 of 60 Trailer specifications	e.) The opening & fixing arrangement of the canopy shall be such that it does not open beyond 120 degree for which suitable sliding stands on side board on both sides shall be provided. These sliding stands shall also be used to keep the canopy open at 70 to 80 degree during operation.	e) Foldable canopy stand of adequate strength to keep the canopy at 70 top 80 degree open position during operation and suitable stopper arrangement to keep the canopy open at 120 degree during maintenance should be provided.
AA: Clause B) point k) Page 5 of 60 Trailer specifications (Axle)	k.) Axle: Suitable round cross-section axle to take load of min. 1500 Kg. Suitable wheel stud and bolts shall be provided to lock the wheel. Position of axle shall be approx. 250 mm away from the centre of the trailer platform towards the rear.	k.) Axle: Suitable round cross-section axle to take load of min. 1500 Kg. Suitable wheel stud and bolts shall be provided to lock the wheel. Position of the axle should be given adequate offset from the centre point of the trailer in order to balance the load as well as allow for ease of manual lifting from the hook end side.

All other Terms & Conditions of the Bid Document remain unaltered.

sd/-

Tushar Ranjan Dutta

Manager Materials (FD)

For GM-Materials

For Resident Chief Executive