

OIL INDIA LIMITED
(A Government of India Enterprise)
P.O. Duliajan, Pin - 786602
Dist-Dibrugarh, Assam

AMENDMENT NO. 2 DATED 24.11.2018
TO TENDER NO SSG9342P19/03

1.0 This Amendment no. 2 dated 24.11.2018 to tender no. SSG9342P19/03 for supply of **2.1/8" DEEP PENETRATING CHARGE & ACCESSORIES** is issued to incorporate the following changes in the tender

S/N	Clause No.	Existing Notes	Revised Notes
1	Standard Notes: Point NO. 9.0	Quantity against Item 90(Firing Head/Top sub) is calculated for 188 runs of perforations (4m each @ 6 spf), assuming each Firing Head will be used for 10 runs of perforations. If additional quantity of Item 90 is required, the bidder must quote for the same. During field operations, if it is found that the Firing Head gets damaged before completing 10 Runs each, then the bidder must supply the necessary quantity free of charge to OIL. The bidder must confirm it along with their bid	Quantity against Item 90(Firing Head/Top sub) is calculated for 188 runs of perforations (4m each @ 6 spf), assuming each Firing Head will be used for 10 runs of perforations. If additional quantity of Item 90 is required, the bidder must quote for the same.
2	Standard Notes: Point NO. 11.0	The API 'RP- 19-B' data sheet for Item No: 10 must be submitted with the bid and it must be signed and stamped by	The API 'RP- 19-B' data sheet for Item No: 10 must be submitted with the bid and it must be signed and stamped by API approved

		API approved Inspector/officials.	Inspector/officials. <i>Note: If API 'RP- 19-B' data sheet for Item No: 10 cannot be provided, then API RP-43, signed and stamped by API approved Inspector/ Officials, is also acceptable.</i>
3	Standard Notes: Point NO. 15.0	New Point	<u>Note against Item No. 10</u> Material Code: 70025502: 2-1/8 inch TTP Charge having T.T. Penetration =27.49 inches min. normalized to 5000 psi is also acceptable provided all other specifications satisfy the tender requirements.
4	Standard Notes: Point NO. 16.0	New Point	<u>Note against Item No. 30 (</u> Material Code: 70024246 <u>);</u> Detonating Cord HMX 80 gr/ ft. Rilsan/Teflon or equivalent Jacketed Low shrink (1% Max.) 100% inspected, recommended to be used in exposed condition and having Temperature rating of 375 degree F is also acceptable provided all other specifications satisfy the tender requirements.

2.0 All other terms and condition of the tender will remain unchanged.

sd-
Gitasree Sarmah
Manager Materials (FS)
For GM MATERIALS
For Resident Chief Executive