

OIL INDIA LIMITED
(A Government of India Enterprise)
P.O. Duliajan, Pin – 786602
Dist-Dibrugarh, Assam

CORRIGENDUM

Amendment No. 03 Dated 18.03.2020
to Tender No. SDG3602P20/06 dated 28.01.2020

1.0 This Amendment No. 01 dated 18.03.2020 to Tender No. SDG3602P20/06 is issued to amend the following technical specifications of NIT item no 10 item description instead of existing:

Clause No	Old Material Description	Amended Material Description
10	<p>Double plug cementing head for 9.5/8” casing: 01 Number</p> <p>Double plug container cementing head with quick latch coupler for 9.5/8”(244.475mm) OD casing comprising with following features & parts.</p> <p>Other Features: a) Suitable for 9.5/8 inch (244.475mm) OD API threaded and coupled casing joints.</p> <p>b) Working pressures of the Cementing Head not less than 5000 PSI (351.53 kg/cm²) and Test pressure not less than 7500 PSI (527.30 kg/cm²).</p> <p>c) Feature of integral quick latch coupler that allows safe & quick installation of the plug container /casing assembly.</p> <p>d) Plug container featured with levelling bar to mitigate uneven weight distribution for a safer, easier installation of the plug container.</p> <p>e) Featured with manifold utilizing Lo torque plug valves.</p> <p>f) The cementing head should</p>	<p>Double plug cementing head for 9.5/8” casing: 01 Number</p> <p>Double plug container cementing head with quick latch coupler for 9.5/8”(244.475mm) OD casing comprising with following features & parts.</p> <p>Other Features: a) Suitable for 9.5/8 inch (244.475mm) OD API threaded and coupled casing joints.</p> <p>b) Working pressures of the Cementing Head not less than 5000 PSI (351.53 kg/cm²) and Test pressure not less than 7500 PSI (527.30 kg/cm²).</p> <p>c) Feature of integral quick latch coupler that allows safe & quick installation of the plug container /casing assembly.</p> <p>d) Plug container featured with levelling bar to mitigate uneven weight distribution for a safer, easier installation of the plug container.</p> <p>e) Featured with manifold utilizing Lo torque plug valves.</p> <p>f) The cementing head should</p>

	<p>include a lifting swivel & has a seamless, weldless cap with bar holes for easy make up.</p> <p>h) The cementing head should have an external plug indicator assembly to indicate when wiper plugs have left the cementing head.</p> <p>i) Suitable for all types of cementing plugs used for 9.5/8 inch (244.475mm), 47- 53.5 ppf API casings.</p> <p>j) Approximate dimensions of the cementing head:</p> <p>a) Length : 63 inches (1600.2 mm), Approx. b) Weight: 1000 kg, Approx.</p> <p>Qty: 01 Number</p>	<p>include a lifting swivel & has a seamless, weldless cap with bar holes for easy make up.</p> <p>h) The cementing head should have an external plug indicator assembly to indicate when wiper plugs have left the cementing head.</p> <p>i) Suitable for all types of cementing plugs used for 9.5/8 inch (244.475mm), 47- 53.5 ppf API casings.</p> <p>j) Approximate dimensions of the cementing head:</p> <p>a) Length : 56 inches-66 inches (1422 mm- 1676.4 mm) b) Weight: 1000 kg, Approx.(Indicative)</p> <p>Qty: 01 Number</p>
--	--	--

2.0 All other Terms & Conditions of the Bid Document remain unaltered.

sd/-
Kumar Abhimanyu
Materials Manager (FD)
For GM-Materials
For Resident Chief Executive