

**OIL INDIA LIMITED**  
(A Government of India Enterprise)  
P.O. Duliajan, Pin – 786602  
Dist-Dibrugarh, Assam

**CORRIGENDUM**

**ADDENDUM No.01 Dated 15.12.2016**

**To**

**Tender No. SDG3003P17/06**

This Addendum No.01 dated 15.12.2016 to **Tender No. SDG3003P17/06** for supply of **Collar Type Elevator** is issued to :

**AA) Amendment to Technical clauses as given below:**

<b>Sl.No.</b>	<b>Tender Requirements</b>	<b>Amended Requirements</b>
Item No 10	<p>SINGLE JOINT COLLAR TYPE CENTER LATCH ELEVATOR FOR HANDLING <b>4.1/2 INCH (114.3 MM) TO 5 INCH (127 MM) OD CASING</b>, 4 TON CAPACITY- 6 Nos.</p> <p>Single joint collar type elevator, Varco BJ type SJL or equivalent for handling 4.1/2 inch (114.3 mm) to 5 inch (127 mm) OD casing, capacity 4 Ton, complete with swivel suspension assembly of 4 ton capacity.</p> <p>Elevator should be made from high quality alloy steel, fully heat treated, equipped with easy and safe operating handles, latch and safety lock combination, Link ears in conformance to API elevator links manufactured strictly as per API 8C (latest edition) PSL2.</p>	<p>SINGLE JOINT COLLAR TYPE CENTER LATCH ELEVATOR FOR HANDLING <b>5 INCH (127 MM) OD CASING</b>, MINIMUM 4 TON CAPACITY- 6 Nos.</p> <p>Single joint collar type elevator, Varco BJ type SJL or equivalent for handling 5 inch (127 mm) OD casing, minimum capacity 4 Ton, complete with swivel suspension assembly of minimum 4 ton capacity.</p> <p>Elevator should be made from high quality alloy steel, fully heat treated, equipped with easy and safe operating handles, latch and safety lock combination, manufactured strictly as per API 8C (latest edition) PSL2.</p>
Item No 20	<p>COLLAR TYPE SIDE DOOR ELEVATOR FOR HANDLING <b>4.1/2 INCH (114.3 MM) TO 5 INCH (127 MM) OD CASING</b>, 150 TON CAPACITY, 4 Nos.</p> <p>Side Door COLLAR TYPE 90 degree shouldered Elevator made from high quality alloy steel, fully heat treated, equipped with easy and safe operating handles, latch and safety lock</p>	<p>COLLAR TYPE SIDE DOOR ELEVATOR FOR HANDLING <b>5 INCH (127 MM) OD CASING</b>, 150 TON CAPACITY, 4 Nos.</p> <p>Side Door COLLAR TYPE 90 degree shouldered Elevator made from high quality alloy steel, fully heat treated, equipped with easy and safe operating handles, latch and safety lock</p>

	<p>combination, Link ears in conformance to API elevator links, handle at rear and having proper balance for handling 4.1/2 inch(114.3 mm) to 5 inch (127 mm) OD Casing. The item should be manufactured strictly as per API 8C (latest edition) PSL2 with 150 Ton rated capacity</p>	<p>combination, Link ears in conformance to API elevator links, handle at rear and having proper balance for handling 5 inch (127 mm) OD Casing. The item should be manufactured strictly as per API 8C (latest edition) PSL2 with 150 Ton rated capacity</p>
--	---	---

\*\*All other Terms & Conditions of the Bid Document remain unaltered.

sd/-  
Chandana Phukan  
Purchase Officer (FD)  
For Dy. GM Materials  
For Resident Chief Executive