



OIL INDIA LIMITED
(A Govt. of India Enterprise)
P.O. Duliajan – 786602, Assam

Telephone No. (91-374) 2808705
Fax No: (91-374) 2800533
Email: km_kumar@oilindia.in ; erp_mm@oilindia.in

Tender No. & Date : **SDG2462P20/07 dated: 11.09.2019**

Bid Security Amount : **INR 6,53,900.00 OR USD 9,344.00**

Bidding Type : **SINGLE STAGE TWO BID SYSTEM**

Bid Closing on : **06.11.2019 (at 11.00 Hrs. IST)**

Bid Opening on : **06.11.2019 (at 14.00 Hrs. IST)**

Bid Validity : **Bid should be valid for 120 days from bid Closing date**

Bid Bond Validity : **Bid Bond should be valid up to 06.06.2020**

Performance Guarantee : **Applicable @ 10% of Order value**

Integrity Pact : **Applicable**

List of Annexures Applicable : **ANNEXURE-A: Specifications, General & Special notes to bidders**
ANNEXURE-B: Bid Evaluation & Rejection Criteria
ANNEXURE-C: Check List-Commercial & Technical
ANNEXURE-D: Certificate of Annual Turnover & NetWorth
ANNEXURE-E: Technical Evaluation Matrix (Technical Specs.)
ANNEXURE-F: Technical Evaluation Matrix (BEC / BRC)
FORMAT A- Format of undertaking by Bidders towards submission of authentic Information /document

AA:: (I) MATERIAL DESCRIPTION, TECHNICAL SPECIFICATIONS & QUANTITY:

ITEM NO.	MATERIAL DESCRIPTION, TECHNICAL SPECIFICATIONS	QUANTITY
10	<p>HAND SLIP FOR 2.3/8 INCHES OD DRILL PIPE</p> <p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p> <p>1) Rotary hand slip 88.90 mm (3.1/2 inches) Body complete with Elastomer Flex handles & inserts for 60.325 mm (2.3/8 inches) OD drill pipe. Hand slip should have an API taper of 4 inch/ft. & suitable for use in 17.1/2 inches Square drive Rotary Table.</p> <p>2) Minimum Load bearing capacity of the Rotary Hand Slip should be not less than 150 Ton.</p> <p>3) The supporting slips should have minimum 11 inches (279.40 mm) gripping length.</p> <p>4) The slips should be manufactured from high quality alloy steel; fully heat treated and should strictly conform to API 7K (latest edition).</p> <p>5) Mass Slip weight i.e. weight of the complete slip with inserts and handles should be within 150 pounds (Maximum)</p> <p>6) Extra set of Inserts for each slip - 2 Set (Total 8 Sets).</p> <p>7) Extra Elastomer Flex Handle for each slip - 2 Numbers (Total 8 Nos).</p> <p>B. SPECIAL REQUIREMENTS:</p> <p>1) SR-1 Proof Load Test: The items (HAND SLIP FOR 2.3/8 INCHES OD DRILL PIPE) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K – Annex A.2). Test reports should be submitted along with the supply.</p> <p>2) SR-3 Data Book: The Manufacturer’s Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply.</p>	04 (FOUR) NUMBERS
20	<p>HAND SLIP FOR 2.7/8 INCHES OD DRILL PIPE</p> <p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p>	06 (SIX) NUMBERS

	<p>1) Rotary hand slip 88.90 mm (3.1/2 inches) Body complete with Elastomer Flex handles & inserts for 73.025 mm (2.7/8 inches) OD drill pipe. Hand slip should have an API taper of 4 inch/ft. & suitable for use in 17.1/2 inches Square drive Rotary Table.</p> <p>2) Minimum Load bearing capacity of the Rotary Hand Slip should be not less than 150 Ton.</p> <p>3) The supporting slips should have minimum 11 inches (279.40 mm) gripping length.</p> <p>4) The slips should be manufactured from high quality alloy steel; fully heat treated and should strictly conform to API 7K (latest edition).</p> <p>5) Mass Slip weight i.e. weight of the complete slip with inserts and handles should be within 150 pounds (Maximum)</p> <p>6) Extra set of Inserts for each slip - 2 Set (Total 12 Sets).</p> <p>7) Extra Elastomer Flex Handle for each slip - 2 Numbers (Total 12 Nos).</p> <p>B. SPECIAL REQUIREMENTS:</p> <p>1) SR-1 Proof Load Test: The items (HAND SLIP FOR 2.7/8 INCHES OD DRILL PIPE) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K – Annex A.2). Test reports should be submitted along with the supply.</p> <p>2) SR-3 Data Book: The Manufacturer’s Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply.</p>	
30	<p>HAND SLIP FOR 4.1/2 INCHES OD DRILL PIPE</p> <p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p> <p>1) Rotary hand slip 127.00 mm (5 inches) Body complete with Elastomer Flex handles & inserts for 114.30 mm (4.1/2 inches) OD drill pipe. Hand slip should have an API taper of 4 inch/ft. & suitable for use in 27.1/2 inches Square drive Rotary Table.</p> <p>2) Minimum Load bearing capacity of the Rotary Hand Slip should be not less than 350 Ton.</p> <p>3) The supporting slips should have minimum 13.3/4 inches (349.25 mm) gripping length.</p>	04 (FOUR) NUMBERS

	<p>4) The slips should be manufactured from high quality alloy steel; fully heat treated and should strictly conform to API 7K (latest edition).</p> <p>5) Mass Slip weight i.e. weight of the complete slip with inserts and handles should be within 200 pounds (Maximum)</p> <p>6) Extra set of Inserts for each slip - 2 Set (Total 8 Sets).</p> <p>7) Extra Elastomer Flex Handle for each slip - 2 Numbers (Total 8 Nos).</p> <p>B. SPECIAL REQUIREMENTS:</p> <p>1) SR-1 Proof Load Test: The items (HAND SLIP FOR 4.1/2 INCHES OD DRILL PIPE) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K – Annex A.2). Test reports should be submitted along with the supply.</p> <p>2) SR-3 Data Book: The Manufacturer’s Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply.</p>	
40	<p>HAND SLIP FOR 5 INCHES OD DRILL PIPE</p> <p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p> <p>1) Rotary hand slip 127.00 mm (5 inches) Body complete with Elastomer Flex handles & inserts for 127.00 mm (5 inches) OD drill pipe. Hand slip should have an API taper of 4 inch/ft. & suitable for use in 27.1/2 inches Square drive Rotary Table.</p> <p>2) Minimum Load bearing capacity of the Rotary Hand Slip should be not less than 350 Ton.</p> <p>3) The supporting slips should have minimum 13.3/4 inches (349.25 mm) gripping length.</p> <p>4) The slips should be manufactured from high quality alloy steel; fully heat treated and should strictly conform to API 7K (latest edition).</p> <p>5) Mass Slip weight i.e. weight of the complete slip with inserts and handles should be within 200 pounds (Maximum)</p> <p>6) Extra set of Inserts for each slip - 2 Set (Total 12 Sets).</p> <p>7) Extra Elastomer Flex Handle for each slip - 2 Numbers (Total 12</p>	<p>06 (SIX) NUMBERS</p>

	<p>Nos).</p> <p>B. SPECIAL REQUIREMENTS:</p> <p>1) SR-1 Proof Load Test: The items (HAND SLIP FOR 5 INCHES OD DRILL PIPE) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K – Annex A.2). Test reports should be submitted along with the supply.</p> <p>2) SR-3 Data Book: The Manufacturer’s Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply.</p>	
50	<p>HAND SLIP FOR 8 INCHES OD DRILL COLLAR</p> <p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p> <p>1) Multi-segment Forged Drill Collar Rotary Hand Slip for 8 inches OD Drill Collars complete with Circular Buttons and handles. Hand slip should have an API taper of 4 inch/ft. & suitable for use in 27.1/2" Square drive Rotary Table.</p> <p>2) Minimum Load bearing capacity of the Rotary Hand Slip should be not less than 150 Ton.</p> <p>3) The supporting slips should have minimum 9 inches (228.60 mm) gripping length.</p> <p>4) The slips should be manufactured from high quality alloy steel; fully heat treated and should strictly conform to API 7K (latest edition).</p> <p>5) The handles should be flexible type and centre handle to be provided for better handling of the equipment.</p> <p>6) Mass Slip weight i.e. weight of the complete slip with inserts and handles should be within 200 pounds (Maximum)</p> <p>7) Extra Set of Circular Buttons for each slip - 2 Set (Total 10 Sets).</p> <p>8) Extra Elastomer Flex Handle for each slip - 2 Numbers (Total 10 Nos).</p> <p>B. SPECIAL REQUIREMENTS:</p> <p>1) SR-1 Proof Load Test: The items (HAND SLIP FOR 8 INCHES OD DRILL COLLAR) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K –</p>	<p>05 (FIVE) NUMBERS</p>

	<p>Annex A.2). Test reports should be submitted along with the supply.</p> <p>2) SR-3 Data Book: The Manufacturer's Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply.</p>	
60	<p>HAND SLIP FOR 9.1/2 INCHES OD DRILL COLLAR</p> <p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p> <ol style="list-style-type: none"> 1) Multi-segment Forged Drill Collar Rotary Hand Slip for 9.1/2 inches OD Drill Collars complete with Circular Buttons and handles. Hand slip should have an API taper of 4 inch/ft. & suitable for use in 27.1/2" Square drive Rotary Table. 2) Minimum Load bearing capacity of the Rotary Hand Slip should be not less than 150 Ton. 3) The supporting slips should have minimum 9 inches (228.60 mm) gripping length. 4) The slips should be manufactured from high quality alloy steel; fully heat treated and should strictly conform to API 7K (latest edition). 5) The handles should be flexible type and centre handle to be provided for better handling of the equipment. 6) Mass Slip weight i.e. weight of the complete slip with inserts and handles should be within 200 pounds (Maximum) 7) Extra Set of Circular Buttons for each slip - 2 Set (Total 12 Sets). 8) Extra Elastomer Flex Handle for each slip - 2 Numbers (Total 12 Nos). <p>B. SPECIAL REQUIREMENTS:</p> <ol style="list-style-type: none"> 1) SR-1 Proof Load Test: The items (HAND SLIP FOR 9.1/2 INCHES OD DRILL COLLAR) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K – Annex A.2). Test reports should be submitted along with the supply. 2) SR-3 Data Book: The Manufacturer's Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply. 	<p>06 (SIX) NUMBERS</p>

70	<p>HAND SLIP FOR 2.7/8 INCHES OD EU TUBING</p> <p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p> <ol style="list-style-type: none"> 1) Rotary hand slip 88.90 mm (3.1/2 inches) Body complete with Elastomer Flex handles & inserts for 73.025 mm (2.7/8 inches) OD EU tubing. Hand slip should have an API taper of 4 inch/ft. & suitable for use in 27.1/2 inches Square drive Rotary Table. 2) Minimum Load bearing capacity of the Rotary Hand Slip should be not less than 150 Ton. 3) The supporting slips should have minimum 11 inches (279.40 mm) gripping length. 4) The slips should be manufactured from high quality alloy steel; fully heat treated and should strictly conform to API 7K (latest edition). 5) Mass Slip weight i.e. weight of the complete slip with inserts and handles should be within 150 pounds (Maximum) 6) Extra set of Inserts for each slip - 2 Set (Total 20 Sets). 7) Extra Elastomer Flex Handle for each slip - 2 Numbers (Total 20 Nos). <p>B. SPECIAL REQUIREMENTS:</p> <ol style="list-style-type: none"> 1) SR-1 Proof Load Test: The items (HAND SLIP FOR 2.7/8 INCHES OD EU TUBING) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K – Annex A.2). Test reports should be submitted along with the supply. 2) SR-3 Data Book: The Manufacturer’s Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply. 	10 (TEN) NUMBERS
80	<p>HAND SLIP FOR 20 INCHES OD CASING</p> <p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p> <ol style="list-style-type: none"> 1) Extra long Casing hand slips complete with handles & circular buttons for 508 mm (20 inches) OD casing pipes. Hand slip should have an API taper of 4 inch/ft. 2) Extra set of circular buttons for each slip - 1 set (Total 04 sets) 	04 (FOUR) NUMBERS

	<p>3) Minimum load bearing capacity of the casing hand slips should not be less than 250 tons.</p> <p>4) The supporting slips should have minimum 13 inches (330.20 mm) gripping length and should provide maximum circumferential grip for uniform pressure around the casing.</p> <p>5) The handles should be flexible type and centre handle to be provided for better handling of the equipment.</p> <p>B. SPECIAL REQUIREMENTS:</p> <p>1) SR-1 Proof Load Test: The items (HAND SLIP FOR 20 INCHES OD CASING) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K – Annex A.2). Test reports should be submitted along with the supply.</p> <p>2) SR-3 Data Book: The Manufacturer’s Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply.</p>	
90	<p>HAND SLIP FOR 13.3/8 INCHES OD CASING</p> <p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p> <p>1) Extra long Casing hand slips complete with handles & circular buttons for 339.725 mm (13.3/8 inches) OD casing pipes. Hand slip should have an API taper of 4 inch/ft.</p> <p>2) Extra set of circular buttons for each slip - 1 set (Total 06 sets)</p> <p>3) Minimum load bearing capacity of the casing slips should not be less than 450 Tons.</p> <p>4) The supporting slips should have minimum 13 inches (330.20 mm) gripping length and should provide maximum circumferential grip for uniform pressure around the casing.</p> <p>5) The handles should be flexible type and centre handle to be provided for better handling of the equipment.</p> <p>B. SPECIAL REQUIREMENTS:</p> <p>1) SR-1 Proof Load Test: The items (HAND SLIP FOR 13.3/8 INCHES OD CASING) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K –</p>	<p>06 (SIX) NUMBERS</p>

	<p>Annex A.2). Test reports should be submitted along with the supply.</p> <p>2) SR-3 Data Book: The Manufacturer's Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply.</p>	
100	<p>HAND SLIP FOR 9.5/8 INCHES OD CASING</p> <p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p> <ol style="list-style-type: none"> 1) Extra long Casing hand slips complete with handles & circular buttons for 244.475 mm (9.5/8 inches) OD casing pipes. Hand slip should have an API taper of 4 inch/ft. 2) Extra set of circular buttons for each slip - 1 set (Total 07 sets) 3) Minimum load bearing capacity of the casing slips should not be less than 450 Tons. 4) The supporting slips should have minimum 13 inches (330.20 mm) gripping length and should provide maximum circumferential grip for uniform pressure around the casing. 5) The handles should be flexible type and centre handle to be provided for better handling of the equipment. <p>B. SPECIAL REQUIREMENTS:</p> <ol style="list-style-type: none"> 1) SR-1 Proof Load Test: The items (HAND SLIP FOR 9.5/8 INCHES OD CASING) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K – Annex A.2). Test reports should be submitted along with the supply. 2) SR-3 Data Book: The Manufacturer's Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply. 	07 (SEVEN) NUMBERS
110	<p>HAND SLIP FOR 5.1/2 INCHES OD CASING</p> <p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p> <ol style="list-style-type: none"> 1) Multi-segment Forged Rotary Hand Slip for 5.1/2 inches OD Casing complete with Circular Buttons and handles. Hand slip should have an API taper of 4 inch/ft. & suitable for use in 27.1/2" Square drive Rotary Table. 2) Minimum Load bearing capacity of the Rotary Hand Slip should 	06 (SIX) NUMBERS

	<p>be not less than 150 Ton.</p> <p>3) The supporting slips should have minimum 9 inches (228.60 mm) gripping length.</p> <p>4) The slips should be manufactured from high quality alloy steel; fully heat treated and should strictly conform to API 7K (latest edition).</p> <p>5) The handles should be flexible type and centre handle to be provided for better handling of the equipment.</p> <p>6) Mass Slip weight i.e. weight of the complete slip with inserts and handles should be within 175 pounds (Maximum)</p> <p>7) Extra Set of Circular Buttons for each slip - 2 Set (Total 12 Sets).</p> <p>8) Extra Elastomer Flex Handle for each slip - 2 Numbers (Total 12 Nos).</p> <p>B. SPECIAL REQUIREMENTS:</p> <p>1) SR-1 Proof Load Test: The items (HAND SLIP FOR 5.1/2 INCHES OD CASING) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K – Annex A.2). Test reports should be submitted along with the supply.</p> <p>2) SR-3 Data Book: The Manufacturer’s Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply.</p>	
120	<p>HAND SLIP FOR 7 INCHES OD CASING</p> <p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p> <p>1) Extra long Casing hand slips complete with handles & circular buttons for 177.80 mm (7 inches) OD casing pipes. Hand slip should have an API taper of 4 inch/ft.</p> <p>2) Extra set of circular buttons for each slip - 1 set (Total 04 sets)</p> <p>3) Minimum load bearing capacity of the casing slips should not be less than 350 Tons.</p> <p>4) The supporting slips should have minimum 13 inches (330.20 mm) gripping length and should provide maximum circumferential grip for uniform pressure around the casing.</p> <p>5) The handles should be flexible type and centre handle to be</p>	<p>04 (FOUR) NUMBERS</p>

	<p>provided for better handling of the equipment.</p> <p>B. SPECIAL REQUIREMENTS:</p> <p>1) SR-1 Proof Load Test: The items (HAND SLIP FOR 7 INCHES OD CASING) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K – Annex A.2). Test reports should be submitted along with the supply.</p> <p>2) SR-3 Data Book: The Manufacturer’s Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply.</p>	
130	<p>HAND SLIP FOR 3.1/2 INCHES OD DRILL COLLAR</p> <p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p> <p>1) Multi-segment Forged Drill Collar Rotary Hand Slip for 3.1/2 inches OD Drill Collars complete with Circular Buttons and handles. Hand slip should have an API taper of 4 inch/ft. & suitable for use in 27.1/2" Square drive Rotary Table.</p> <p>2) Minimum Load bearing capacity of the Rotary Hand Slip should be not less than 150 Ton.</p> <p>3) The supporting slips should have minimum 7.7/8 inches (200.025 mm) gripping length.</p> <p>4) The slips should be manufactured from high quality alloy steel; fully heat treated and should strictly conform to API 7K (latest edition).</p> <p>5) The handles should be flexible type and centre handle to be provided for better handling of the equipment.</p> <p>6) Mass Slip weight i.e. weight of the complete slip with inserts and handles should be within 125 pounds (Maximum)</p> <p>7) Extra Set of Circular Buttons for each slip - 2 Set (Total 6 Sets).</p> <p>8) Extra Elastomer Flex Handle for each slip - 2 Numbers (Total 6 Nos).</p> <p>B. SPECIAL REQUIREMENTS:</p> <p>1) SR-1 Proof Load Test: The items (HAND SLIP FOR 3.1/2 INCHES OD DRILL COLLAR) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API</p>	03 (THREE) NUMBERS

	<p>Specification 7K – Annex A.2). Test reports should be submitted along with the supply.</p> <p>2) SR-3 Data Book: The Manufacturer’s Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply.</p>	
140	<p>HAND SLIP FOR 4.3/4 INCHES OD DRILL COLLAR</p> <p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p> <ol style="list-style-type: none"> 1) Multi-segment Forged Drill Collar Rotary Hand Slip for 4.3/4 inches OD Drill Collars complete with Circular Buttons and handles. Hand slip should have an API taper of 4 inch/ft. & suitable for use in 27.1/2" Square drive Rotary Table. 2) Minimum Load bearing capacity of the Rotary Hand Slip should be not less than 150 Ton. 3) The supporting slips should have minimum 7.7/8 inches (200.025 mm) gripping length. 4) The slips should be manufactured from high quality alloy steel; fully heat treated and should strictly conform to API 7K (latest edition). 5) The handles should be flexible type and centre handle to be provided for better handling of the equipment. 6) Mass Slip weight i.e. weight of the complete slip with inserts and handles should be within 125 pounds (Maximum) 7) Extra Set of Circular Buttons for each slip - 2 Set (Total 4 Sets). 8) Extra Elastomer Flex Handle for each slip - 2 Numbers (Total 4 Nos). <p>B. SPECIAL REQUIREMENTS:</p> <ol style="list-style-type: none"> 1) SR-1 Proof Load Test: The items (HAND SLIP FOR 4.3/4 INCHES OD DRILL COLLAR) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K – Annex A.2). Test reports should be submitted along with the supply. 2) SR-3 Data Book: The Manufacturer’s Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply. 	02 (TWO) NUMBERS

150	<p>HAND SLIP FOR 6.1/2 INCHES OD DRILL COLLAR</p> <p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p> <ol style="list-style-type: none"> 1) Multi-segment Forged Drill Collar Rotary Hand Slip for 6.1/2 inches OD Drill Collars complete with Circular Buttons and handles. Hand slip should have an API taper of 4 inch/ft. & suitable for use in 27.1/2" Square drive Rotary Table. 2) Minimum Load bearing capacity of the Rotary Hand Slip should be not less than 150 Ton. 3) The supporting slips should have minimum 9 inches (228.60 mm) gripping length. 4) The slips should be manufactured from high quality alloy steel; fully heat treated and should strictly conform to API 7K (latest edition). 5) The handles should be flexible type and centre handle to be provided for better handling of the equipment. 6) Mass Slip weight i.e. weight of the complete slip with inserts and handles should be within 175 pounds (Maximum) 7) Extra Set of Circular Buttons for each slip - 2 Set (Total 16 Sets). 8) Extra Elastomer Flex Handle for each slip - 2 Numbers (Total 16 Nos). <p>B. SPECIAL REQUIREMENTS:</p> <ol style="list-style-type: none"> 1) SR-1 Proof Load Test: The items (HAND SLIP FOR 6.1/2 INCHES OD DRILL COLLAR) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K – Annex A.2). Test reports should be submitted along with the supply. 2) SR-3 Data Book: The Manufacturer's Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply. 	08 (EIGHT) NUMBERS
160	<p>HAND SLIP FOR 3.1/2 INCHES OD DRILL PIPE</p> <p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p> <ol style="list-style-type: none"> 1) Rotary hand slip 114.30 mm (4.1/2 inches) Body complete with 	06 (SIX) NUMBERS

	<p>Elastomer Flex handles & inserts for 88.90 mm (3.1/2 inches) OD drill pipe. Hand slip should have an API taper of 4 inch/ft. & suitable for use in 27.1/2 inches Square drive Rotary Table.</p> <p>2) Minimum Load bearing capacity of the Rotary Hand Slip should be not less than 350 Ton.</p> <p>3) The supporting slips should have minimum 13.3/4 inches (349.25 mm) gripping length.</p> <p>4) The slips should be manufactured from high quality alloy steel; fully heat treated and should strictly conform to API 7K (latest edition).</p> <p>5) Mass Slip weight i.e. weight of the complete slip with inserts and handles should be within 210 pounds (Maximum)</p> <p>6) Extra set of Inserts for each slip - 2 Set (Total 12 Sets).</p> <p>7) Extra Elastomer Flex Handle for each slip - 2 Numbers (Total 12 Nos).</p> <p>B. SPECIAL REQUIREMENTS:</p> <p>1) SR-1 Proof Load Test: The items (HAND SLIP FOR 3.1/2 INCHES OD DRILL PIPE) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K – Annex A.2). Test reports should be submitted along with the supply.</p> <p>2) SR-3 Data Book: The Manufacturer’s Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply.</p>	
--	--	--

(II) SPECIAL NOTES TO BIDDERS:

1. The items shall be brand new, unused & of prime quality. Bidder shall warrant (in the event of an order) that the product supplied will be free from all defects & fault in material, workmanship & manufacture and shall be in full conformity with API specification 7K standard (6th Edition). This clause shall be valid for 18 months from date of shipment/dispatch or 12 months from the date of receipt of the items whichever is earlier. The defective materials, if any, rejected by OIL shall be replaced by the supplier at their own arrangements. Bidders must confirm the same in their quotations.

2. The bidder must specify the offered items in details, forwarding relevant product catalogue, literature, detailed drawings with exploded views of each & every item of the offered product with complete spare parts list & clearly indicating the various parts with part numbers.

3. The items are to be designed/manufactured/tested strictly as per API Spec 7K (Latest Edition) and bidders are required to forward valid API 7K specification certificate (having authorization for manufacturing of Rotary Slips) along with the quotation.

Moreover copies of API 7K (having authorization for manufacturing of Rotary Slips) certificates of the manufacturer for the last 5 (Five) years (i.e. continuous without having any break in between), preceding the Original Bid Closing date of the tender, shall be submitted along with techno-commercial bid. Bids without copies of valid relevant API certificates or with break(s) in between will be rejected.

4. Necessary testing and marking shall be done as per API Spec 7K (6th Edition), and as specified elsewhere in the tender. The items shall be die stamped with the manufacturer's name, the API monogram and the month and year of manufacture. Bidders are to confirm the same while quoting.

5. Equipment should be fully radio graphed, ultrasonic tested, proof load tested & MPI. In the event of an order, all relevant testing documents and manufacturers' data book as per API should be submitted along with the delivery of the order. Bidder should confirm the same while quoting.

6. Bidder should indicate the name of manufacturer, country of origin and port of dispatch of the materials.

7. Any deviation(s) from the tender specification should be clearly highlighted specifying justification in support of deviation.

8. Bidder should note that in the event of an order, the API licenses for manufacturing the Rotary Slips along with authorization for API monogramming should be valid, without any break, till execution of purchase order. Valid relevant API certificate to be submitted along with the supply. Bidder should categorically confirm compliance while quoting.

9. Bidder to sign and submit completely filled up Technical Evaluation Matrix for Bid evaluation criteria and Technical specification.

10. Bidder should categorically confirm in the technical bid a delivery schedule within eight (08) months, FOB Port of dispatch, after establishment of letter of credit (in case of foreign bidder) or for dispatch of the equipment within eight (08) months after receipt of formal order (in case of indigenous bidder) failing which their offer will be rejected.

BB :: GENERAL NOTES TO BIDDERS:

Sl. No.	Clause description
1.0	<p>Tender fee is not applicable against this tender.</p> <p><u>Bidders to take note of the following:</u></p> <ol style="list-style-type: none"><u>1.</u> Bidders without having E-tender Login ID and Password should complete their online registration at least seven (7) days prior to the scheduled bid closing date and time of the tender. For online registration, Bidder may visit the OIL's E-tender site https://etender.srm.oilindia.in/irj/portal<u>2.</u> Necessary Login ID& Password will be issued by OIL only after submitting the complete online registration by the Bidder. In the event of late registration/incomplete registration by Bidder, OIL INDIA LIMITED shall not be responsible for late allotment of User ID & Password and request for bid closing date extension on that plea shall not be entertained by Company.<u>3.</u> MSEs Units (manufacturers/Service Providers only and not their dealers/distributors) who are already registered with District Industry Centers or Khadi& Village Industries Commission or Khadi& Village Industries Board or Coir Board or National Small Industries Corporation or Directorate of Handicrafts & Handloom or any other body specified by Ministry of MSME are exempted from payment of Bid Security (EMD) irrespective of monetary limit, product category and capacity mentioned in their registration, subject to submission of valid MSE registration certificate issued by appropriate authority.<u>4.</u> For availing benefits under Public Procurement Policy (Purchase preference & EMD exemption), the interested MSE Bidders must ensure that they are the manufacturer/ service provider of tendered item(s) and registered with the appropriate authority for the said item(s). Bids without EMD shall be rejected, if the technical offer does not include a valid copy of relevant MSE Certificate issued by appropriate authority specifying the item as per tender. Therefore, it is in the interest of such MSE Vendors to furnish a copy of complete certificate to the concerned tender handling officer of OIL at least seven (7) days prior to the scheduled Bid Closing Date of the tender; seeking clarification/confirmation as to whether their registered item is eligible for EMD exemption or not. Late communications in this regard and request for bid closing date extension on that plea shall not be entertained by Company.
2.0	<p>Bid Security/EMD/Performance Bank Guarantee – Must be paid either through online mode or Submission of Bank Guarantee/LC only. No DD/Cheques/Cashier Cheque or any other mode will be acceptable.</p> <p>The Bank Guarantee issued by bank must be routed through SFMS platform as per following details:</p>

	<p>a. (i) “MT760/ MT760 COV for issuance of bank guarantee (ii) MT767/ MT767 COV for amendment of bank guarantee</p> <p>The above message / intimation shall be sent through SFMS by the BG issuing Bank branch to HDFC Bank, Duliajan Branch, IFS Code – HDFC0002118; SWIFT Code - HDFCINBBCAL. Branch Address: HDFC Bank Limited, Duliajan Branch, Utopia Complex, BOC Gate, Jayanagar, Duliajan, Dibrugarh, PIN – 786602.”</p> <p>b. The vendor shall submit to OIL the copy of the SFMS message as sent by the issuing bank branch along with the original bank guarantee.</p>				
3.0	The tender will be governed by “General Terms & Conditions” for e-Procurement as per Booklet No. MM/GLOBAL/E-01/2005 for E-procurement (ICB Tenders) including Amendments & Addendum to “General Terms & Conditions” for e-Procurement.				
4.0	Bid must be submitted online through OIL’s e-procurement portal. Bid submitted in any other form will be rejected.				
5.0	<p>Please note that all tender forms and supporting documents are to be submitted through OIL’s e-Procurement site only except following documents which are to be submitted manually in sealed envelope super scribing tender no. and due date to The GM Materials, Materials Department, Oil India Limited, Duliajan- 786602, Assam on or before 13:00 hrs (IST) on the Bid Closing Date mentioned in the Tender.</p> <p>a) Original Bid Security along with two duplicate copies of Bid Security. b) Any other documents which have been particularly asked for in this tender for submission.</p>				
6.0	Bidders must ensure that their bid is uploaded in the system before the tender closing date and time. Also, they must ensure that above documents which are to be submitted in a sealed envelope are also submitted at the above mentioned address before the bid closing date and time, failing which the offer shall be rejected.				
7.0	<p>The tender is invited under SINGLE STAGE-TWO BID SYSTEM. The bidder has to submit both the “TECHNO-COMMERCIAL UNPRICED BID” and “PRICED BID” through electronic form in the OIL’s e-Tender portal within the Bid Closing Date and Time stipulated in the e-Tender. The “Techno-commercial Unpriced Bid” shall contain all technical and commercial details except the prices which shall be kept blank. Details of prices as per Bid format / Commercial bid to be uploaded as attachment in the Attachment Tab “Notes and Attachments”. Any offer not complying with above submission procedure will be rejected as per Bid Rejection Criteria mentioned in the tender.</p> <div style="margin-top: 10px;"> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="border: 1px solid black; padding: 5px; width: 30%;">Notes and Attachments</td> <td style="padding: 5px;">→ Only Price Details Should Be Uploaded</td> </tr> <tr> <td style="border: 1px solid black; padding: 5px; width: 30%;">Technical attachments</td> <td style="padding: 5px;">→ All technical bid documents except price details</td> </tr> </table> </div>	Notes and Attachments	→ Only Price Details Should Be Uploaded	Technical attachments	→ All technical bid documents except price details
Notes and Attachments	→ Only Price Details Should Be Uploaded				
Technical attachments	→ All technical bid documents except price details				

Please do refer “NEW INSTRUCTION TO BIDDER FOR SUBMISSION” for the above two points and also please refer “ New Vendor Manual (effective 12.04.2017) ” available in the login Page of the OIL’s E-tender Portal.



Click here for the New Manual & Instruction

8.0	<p>In Technical Bid opening, only Technical Rfx will be opened. Therefore, the bidder should ensure that “TECHNO-COMMERCIAL UNPRICED BID should contain details as mentioned in the technical specifications as well as BEC/ BRC and upload the same in the Technical RFX Response-> User - > Technical Bid. <u>No price should be given in above Technical Rfx otherwise the offer will be rejected.</u> Please go through the help document in details before uploading the document and ensure uploading of technical bid in the Technical RFX Response-> User - > Technical Bid only. The “PRICE BID” must contain the price schedule and the bidder’s commercial terms and conditions. Details of prices as per Bid format / Commercial bid can be uploaded as Attachment under the attachment option under “Notes & Attachments”.</p>
9.0	<p>PRICED BIDS OF ONLY THOSE BIDDERS WILL BE OPENED WHOSE OFFERS ARE FOUND TO BE TECHNO-COMMERCIALLY ACCEPTABLE.</p>
10.0	<p>Bidders are requested to examine all instructions, forms, terms and specifications in the bid. Failure to furnish all information required as per the bid or submission of offers not substantially responsive to the bid in every respect will be at the bidders risk and may result in rejection of its offer without seeking any clarifications.</p>
11.0	<p>Please mention clearly in your quotation the Net. Weight, Gross Weight & Volume, Indian Agent's Name and its Commission, Payment Terms, Ocean Freight, Port of Loading, Delivery period, Country of origin with manufacturer's name, etc.</p>
12.0	<p>To ascertain the substantial responsiveness of the bid, OIL reserves the right to ask the bidder for clarification in respect of clauses covered under BRC also and such clarifications fulfilling the BRC clauses in toto must be received on or before the deadline given by OIL, failing which the offer will be summarily rejected.</p>
13.0	<p>Other terms and conditions of the tender shall be as per “General Terms & Conditions” for e- Procurement as per Booklet No. MM/GLOBAL/E-01/2005 for E-procurement (ICB Tenders). However, if any of the Clauses of the Bid Rejection Criteria (BRC) / Bid Evaluation Criteria (BEC) mentioned here contradict the Clauses in the “General Terms & Conditions” for e-Procurement</p>

	as per Booklet No. MM/GLOBAL/E-01/2005 for E-procurement (ICB Tenders) of the tender and/or elsewhere, those mentioned in this BEC / BRC shall prevail.
14.0	All the Bids must be Digitally Signed using “Class 3” [Organization] digital certificate (e-commerce application) only as per Indian IT Act obtained from the licensed Certifying Authorities operating under the Root Certifying Authority of India (RCAI), Controller of Certifying Authorities (CCA) of India. The bid signed using other than “Class 3” [Organization] digital certificate, will be liable for rejection.
15.0	<p>Please do refer the User Manual provided on the portal on the procedure How to create Response for submitting offer.</p> <p>"In order to bid for OIL e-tenders all the vendors are required to obtain a legally valid Digital Certificate Class III [Organization] along with Encryption Certificate as per Indian IT Act from the licensed Certifying Authorities (CA) operating under the Root Certifying Authority of India (RCAI), Controller of Certifying Authorities (CCA) of India. Digital Signature Certificate comes in a pair of Signing/verification and Encryption/decryption certificate. Bidder should have both the Signing/verification and Encryption/Decryption certificate for Signing and encryption, decryption purpose respectively. The driver needs to be installed once, without which the DSC will not be recognized. While participating on e-Tendering the DSC token should be connected to your system.</p> <p>Encryption certificate is mandatorily required for submission of bid. In case bidder created response with one certificate (using encryption key) and bidder change his Digital Signature Certificate then old certificate (used for encryption) is required in order to decrypt his encrypted response for getting the edit mode of the response. Once decryption is done, bidder may use new DSC certificate for uploading and submission of their offer. It is the sole responsibility of the bidder to keep their DSC certificate properly. In case of loss of the certificate, OIL INDIA LTD is not responsible."</p>
16.0	Bidders to note that Govt. of India under Micro, Small and Medium Enterprises Development (MSMED) Act 2006, has proclaimed the Public Procurement Policy, 2012 with effect from 1st April, 2012 in respect of procurement of goods and services, produced and provided by micro and small enterprises, by its Ministries, Departments and Public Sector Undertakings for promotion and development of Micro and Small Enterprises. A new Clause on applicability of Public Procurement Policy for procurement of goods from Micro and Small Enterprises (MSE) in the tender is furnished vide Amendment to General Terms and Conditions for Global Tender (MM/GLOBAL/E-01/2005). Bidders are requested to take note of the same and to submit their offers accordingly.
17.0	The items shall be brand new, unused & of prime quality. Bidder shall warrant (in the event of an order) that the product supplied will be free from all defects & fault in material, workmanship & manufacture and shall be in full conformity with ordered specifications. This clause shall be valid for a period of 18 months from date of shipment / dispatch or 12 months from the date of receipt of the items, whichever is earlier. The defective materials, if any, rejected by OIL shall be replaced by the supplier at their own expense. Bidders must confirm the same in their quotations.
18.0	Quantity of Individual item may be increased or decrease at the time of final placement of order. The minimum FOB charges in case of partial order for reduced quantity/enhanced quantity shall have to be indicated by the bidder. In

	case, this is not indicated specifically, the charges quoted would be pro-rata calculated and the same will be binding on the bidder.
19.0	Any deviation(s) from the tender specification should be clearly highlighted specifying justification in support of deviation.
20.0	<p>The Integrity Pact is applicable against this tender .OIL shall be entering into an Integrity Pact with the bidders as per format enclosed vide Annexure- IX of the tender document. This Integrity Pact proforma has been duly signed digitally by OIL's competent signatory. The proforma has to be returned by the bidder (along with the technical bid) duly signed (digitally) by the same signatory who signed the bid, i.e., who is duly authorized to sign the bid. Uploading the Integrity Pact with digital signature will be construed that all pages of the Integrity Pact has been signed by the bidder's authorized signatory who sign the Bid. If any bidder refuses to sign Integrity Pact or declines to submit Integrity Pact with the offer, their bid shall be rejected straightway.</p> <p>OIL's Independent External Monitors at present are as under:</p> <p>SHRI RAJIV MATHUR, IPS (Retd.), Former Director (IB) Govt. of India e-Mail ID : rajivmathur23@gmail.com</p> <p>SHRI RUDHRAGANGADHARAN, IAS (Retd.) Ex-Secretary, Ministry of Agriculture E-mail Id :rudhra.gangadharan@gmail.com</p> <p>SHRI JAGMOHAN GARG, Ex-Vigilance Commissioner, CVC e-Mail id : jagmohan.garg@gmail.com</p>
21.0	Original Bid Closing Date shall be considered by OIL for evaluation of BRC Criteria in case of any extension of the original bid closing date.
22.0	<p>Performance Security clause (Clause No. 10.0 of Section-A) of "General Terms & Conditions for Global Tenders (MM/GLOBAL/01/2005)" has been amended and the new clause is detailed in the Amendment dated 25.04.2016 issued to MM/GLOBAL/01/2005. Successful bidder will be required to furnish a Performance Bank Guarantee @10% of the order value which should remain valid for the period execution, including extension, if any and the entire warranty period in line with tender requirement. The successful bidder shall submit Performance Security within 30 days of award, failing which OIL reserves the right to cancel the order and forfeit their Bid Security. Bidders should undertake in their bids to submit Performance Security as stated above. Bidders to note the same and to confirm its acceptance in their offers.</p> <p>The Bank Guarantee issued by bank must be routed through SFMS platform as per following details:</p> <p>a. (i) "MT760/ MT760 COV for issuance of bank guarantee (ii) MT767/ MT767 COV for amendment of bank guarantee</p> <p>The above message / intimation shall be sent through SFMS by the BG issuing Bank branch to HDFC Bank, Duliajan Branch, IFS Code – HDFC0002118;</p>

	<p>SWIFT Code - HDFCINBBCAL. Branch Address: HDFC Bank Limited, Duliajan Branch, Utopia Complex, BOC Gate, Jayanagar, Duliajan, Dibrugarh, PIN – 786602.”</p> <p>b. The vendor shall submit to OIL the copy of the SFMS message as sent by the issuing bank branch along with the original bank guarantee.</p>
23.0	Bidder to sign and submit completely filled up Technical & Commercial check list.
24.0	Payment terms: Refer to “General Terms & Conditions” for e- Procurement as per Booklet No. MM/GLOBAL/E-01/2005 for E-procurement (ICB Tenders).
25.0	Liquidated Damage: Refer to “General Terms & Conditions” for e-Procurement as per Booklet No. MM/GLOBAL/E-01/2005 for E-procurement (ICB Tenders). In case of deduction of LD, LD amount will be deducted along with applicable rate of GST.
26.0	<p>The items covered by this enquiry shall be used by Oil India Limited in the PEL/ML areas which are issued/renewed after 01/04/99 and hence Nil Customs Duty against CIF valuing INR 1.00 Lakh and above (Or value as per prevailing Govt. policy) & concessional IGST during import will be applicable.</p> <p>In the event of an order on indigenous bidder, OIL will issue Project Authority Certificate (PAC) under Deemed Export benefit, where import content is declared by the bidder for availing Advance Licence for intermediate Supply. However, Indian bidders will not be issued Recommendatory Letter. Details of Deemed Export benefit are furnished vide Addendum to “General Terms & Conditions” Booklet No. MM/GLOBAL/E-01/2005. The bidders are requested to check the latest position on the subject on their own and OIL shall not accept any liability, whatsoever, on this account.</p> <p>Indigenous Supplier shall furnish the invoice to OIL before the dispatch for obtaining Essentiality Certificate from DGH towards concessional rate of GST against invoice valuing INR 1.00 Lakh and above (Or value as per prevailing Govt. policy).</p> <p>Supplier shall arrange to provide all necessary documents to apply for the essentiality certificate on receipt of request from OIL, if any. Further, supplier shall affect dispatch only on receipt of relevant certificates from OIL, failing which all related liabilities shall be to Supplier’s account.</p>
27.0	Bidders to note that Ministry of Petroleum & Natural Gas, Government of India implemented PPLC Policy to provide Purchase Preference (linked with local content) by notification no. Ref. O-27011/44/2016-ONG-II/FP dtd.25.04.2017. A new Clause on applicability of Purchase Preference (linked with local content) policy in the tender is furnished as Annexure-VIII of the tender document. Bidders are requested to take note of the same and to submit their offers accordingly wherever applicable.

Clauses related to GST:

1. For the purposes of levy and imposition of GST, the expressions shall have the following meanings:
 - (a) GST - means any tax imposed on the supply of goods and/or services under GST Law.
 - (b) Cess – means any applicable cess, existing or future on the supply of Goods and Services as per Goods and Services Tax (Compensation to States) Act, 2017.
 - (c) GST Law - means IGST Act 2017, CGST Act 2017, UTGST Act, 2017 and SGST Act, 2017 and all related ancillary Rules and Notifications issued in this regard from time to time.
2. The rates quoted by the bidders shall be inclusive of all taxes, duties and levies. However, bidders are required to provide separately the rate and amount of all types of taxes, duties and levies. In case, the quoted information related to various taxes, duties & levies subsequently proves wrong, incorrect or misleading, OIL will have no liability to reimburse the difference in the duty/ tax, if the finally assessed amount is on the higher side and OIL will have to right to recover the difference in case the rate of duty/ taxes finally assessed is on the lower side. Further, bidders have to clearly show the amount of GST separately in the Tax Invoices. Further, it is the responsibility of the bidders to make all possible efforts to make their accounting / IT system GST compliant in order to ensure availability of Input Tax Credit (ITC) to Oil India Ltd.
3. Offers without giving any of the details of the taxes (Including rates and amounts) as specified above will be considered as inclusive of all taxes including GST. When a bidder mentions taxes as extra without specifying the rates & amount, the offer will be loaded with maximum value towards taxes received against the tender for comparison purposes. If the bidder emerges as lowest bidder after such loading, in the event of order on that bidder, taxes mentioned by OIL on the Purchase Order/ Contracts will be binding on the bidder.
4. Bidders are required to pass on the benefit arising out of introduction of GST, including seamless flow of Input Tax Credit, reduction in Tax Rate on inputs as well as final goods by way of reduction of price as contemplated in the provision relating to Anti-Profiteering Measure vide Section 171 of the CGST Act, 2017. Accordingly, for supplies made under GST, the bidders should confirm that benefit of lower costs has been passed on to OIL by way of lower prices/taxes and also provide details of the same as applicable. OIL reserves the right to examine such details about costs of inputs/input services of the bidders to ensure that the intended benefits of GST have been passed on to OIL.
5. Oil India Ltd. shall declare the value of free issue of materials and services, if any, involved in the execution of the contract. The Contractor should consider the same while working out the GST liability, if any. Further in cases where GST is leviable on any facilities provided by OIL and used by bidders and the consideration for which is recovered by OIL in the form of reduction in the invoice raised by bidders then OIL will raise GST invoices on such transactions and the same will be reimbursed by bidders.

6. When Input tax credit is available for Set Off

	<p>Evaluation of L-1 prices shall be done based on Quoted price after deduction of Input Tax Credit (ITC) of GST, if available to OIL.OIL shall evaluate the offers on the basis of the quoted rates only and any claim subsequently by the bidders for additional payment/liability shall not be admitted and has to be borne by the bidders</p> <p>When Input tax credit is NOT available for Set Off</p> <p>Evaluation of L-1 prices shall be done based on Quoted price only. OIL shall evaluate the offers on the basis of the quoted rates only and any claim subsequently by the bidders for additional payment/liability shall not be admitted and has to be borne by the bidders</p> <p>7. Bidders agree to do all things not limited to providing GST compliant Tax Invoices or other documentation as per GST law relating to the supply of goods and/or services covered in the instant contract like raising of and /or acceptance or rejection of credit notes / debit notes as the case may be, payment of taxes, timely filing of valid statutory Returns for the tax period on the Goods and Service Tax Network (GSTN), submission of general information as and when called for by OIL in the customized format shared by OIL in order to enable OIL to update its database etc. that may be necessary to match the invoices on GSTN common portal and enable OIL to claim input tax credit in relation to any GST payable under this Contract or in respect of any supply under this Contract.</p> <p>8. In case Input Tax Credit of GST is denied or demand is recovered from OIL by the Central / State Authorities on account of any non-compliance by bidders, including non-payment of GST charged and recovered, the Vendor/Supplier/Contractor shall indemnify OIL in respect of all claims of tax, penalty and/or interest, loss, damages, costs, expenses and liability that may arise due to such non-compliance. OIL, at its discretion, may also withhold/recover such disputed amount from the pending payments of the bidders.</p>
29.0	<p>Along with the technical bid, bidders must submit duly filled undertaking as per format enclosed vide Format-A as undertaking towards submission of authentic information/documents.</p>
30.0	<p>For convenience of the qualified Bidders and to improve transparency, the rates/costs quoted by bidders against OIL's e-tenders shall be available for online viewing by such Bidders whose price bids are opened by Company. A Bidder can view item-wise rates/ costs of all other such peer bidders against the tender immediately after price bid opening, if the e-tender is floated by Company with PRICE CONDITION. In case the Price-Bid is invited by Company through attachment form under "Notes & Attachment" (i.e., NO PRICE Condition), Bidders must upload their detailed Price-Bid as per the prescribed format under "Notes & Attachment", in addition to filling up the "Total Bid Value" Tab taking into account the cost of all individual line items and other applicable charges like freight, tax, duties, levies etc. Under NO PRICE Condition (i.e., Price Bid in attachment form), the "Total Bid Value" as calculated & quoted by the Bidder shall only be shared amongst the eligible bidders and Company will not assume any responsibility whatsoever towards calculation errors/ omissions therein, if any. Notwithstanding to sharing the "Total Bid Value" or the same is whether filled up by the Bidder or not, Company will evaluate the cost details to ascertain the inter-se-ranking of bidders strictly as per the uploaded attachment and Bid Evaluation Criteria only. Online view of prices as above shall be available to the Bidders only upto seven days from the date of Price-Bid opening of the e-tender.</p>

BID EVALUATION CRITERIA (BEC)/BID REJECTION CRITERIA (BRC)

The bids shall conform to the specifications and terms as well conditions laid out in the tender. Bids will be rejected in case the items offered do not conform to the required parameters stipulated in the technical specifications and to the respective international / national standards wherever stipulated. Notwithstanding the general conformity of the bids to the stipulated specifications and terms & conditions, particularly the following requirements will have to be met by the bidders, without which, the offer will be considered as non-responsive and shall be rejected.

(I) BID REJECTION CRITERIA (BRC)

AA. TECHNICAL :

A. IN CASE THE BIDDER IS A MANUFACTURER:

In case the bidder is a manufacturer of the offered item(s), then bidder must furnish the following documents along with the technical bid failing which the bids will be rejected:

A.1 The bidder should have minimum 5 years continuous experience of manufacturing of Rotary Slips (Hand Slips for Drill Pipes, Tubings, Drill Collars and Casings) conforming to API spec. 7K certification. For this purpose, the period reckoned shall be period prior to the date of original bid closing date of the tender. Copies of API 7K certificates, having authorization for Rotary Slips, for the last 5 (Five) years (i.e. continuous without having any break in between) must be submitted along with techno - commercial bid. Bids without copies of valid API 7K certificates or with a break in between will be rejected.

A.2 The bidder should have manufactured and supplied minimum 50% quantity (to be rounded to next higher whole figure) against each of the tendered item, of same or higher capacity and same or higher sizes, for which the bidder has quoted to any E&P companies/Drilling Contractors/Drilling service providers in the last 5 (five) years as on original bid closing date of the tender (either by themselves or through their sole selling agent/distributor/dealer/supply house).

Documentary evidence in respect of manufacturing and supplying the above mentioned items should be submitted with the technical bid, in the form of copies of relevant signed Purchase Orders along with copies of any of the following documents in respect of satisfactory execution of each of those Purchase Orders failing which the bids will be rejected:

- (i) Signed and sealed Satisfactory supply / completion report (in original on user's letter head) (OR)
- (ii) Bill of Lading (OR)
- (iii) Consignee delivery receipt / challan (OR)
- (iv) Central Excise Gate Pass / Tax Invoice issued under relevant rules of Central Excise / Vat / GST (OR)
- (v) Commercial Invoice / Payment Invoice

Note:

a) The Purchase Order date need not be within 5 (five) years preceding original bid closing date of this tender. However, the execution of supply should be within 5 (five) years preceding original bid closing date of this tender.

b) Original Bid Closing Date shall be considered by OIL for evaluation of BRC Criteria in case of any extension of the original bid closing date.

c) Satisfactory supply / completion report should be issued on company's letterhead with signature and stamp. Originals to be produced for verification on demand of OIL.

A.2.1 In case, for supplementing manufacturer's supply experience criteria (A.2), the manufacturer submits Purchase Order(s) and relevant documents which is through their sole selling agent / distributor / dealer / supply house, then following additional documents are also to be submitted:

a) Copies of signed Purchase Order(s) / Contract agreement(s) between the manufacturer and the sole selling agent / distributor / dealer / supply house and copies of any of the following documents in respect of satisfactory execution of each of those Purchase Order(s) / Contract agreement(s).

i) Bill of Lading (OR)

ii) Commercial Invoice / Payment of Invoice of the OEM (OR)

iii) Central Excise Gate Pass/Tax Invoice issued under relevant rules of Central Excise/Vat/GST.

A.3 The bidder shall confirm that the Rotary Slips will be tested and certified as per API 7K (Latest Edition).

A.4 The bidder must keep API licenses along with authorization for API monogram valid till execution of purchase order and must confirm that the offered product will be supplied with API Monogram.

A.5 In case renewal process of API license is in progress at the time of bidding, the manufacturer should furnish a letter from API to this effect that renewal of the license is under examination with API and is authorized to manufacture the items as per API license and to use API monogram till the renewal for license is issued. The bidder shall also submit an undertaking that delay in renewal of API certificate shall not affect the stipulated delivery schedule of the tender / purchase order.

A.6 Bidder should categorically confirm in the technical bid a delivery schedule within eight (08) months, FOB Port of dispatch, after establishment of letter of credit (in case of foreign bidder) or for dispatch of the equipment within eight (08) months after receipt of formal order (in case of indigenous bidder) failing which their offer will be rejected.

A.7 If the bidder is a manufacturer and have successfully supplied eighteen (18) numbers of Hand Slips for drill pipes of any sizes, twelve (12) numbers of Hand Slips for drill collars of any sizes and fourteen (14) numbers of Hand Slips for casings of any sizes to OIL in the last 05 (five) years as on original bid closing date either by themselves or through their sole selling agent / distributor / dealer / supply house and whose past performance has been satisfactory, the bidder need not satisfy Clause A.2. In this situation the bidder shall have to indicate the Purchase Order (P.O.) No. of OIL in their technical bid.

B. IN CASE THE BIDDER IS NOT A MANUFACTURER:

If the bidder is a sole selling agent / distributor / dealer / supply house of any manufacturer(s), then bidder must furnish the following documents along with the technical bid failing which the bids will be rejected:

B.1 Authorization certificate from the manufacturer(s) (in original on manufacturer's letter head) should be submitted along with the technical bid. This certificate should be valid at the time of bidding and should remain valid during the entire execution period of the order.

B.2 Undertaking from the manufacturer(s) (in original on manufacturer's letter head) guaranteeing supply of items to the bidder in the event of an order on the bidder. This certificate should be valid at the time of bidding and should remain valid during the entire execution period of the order.

B.3 Warranty backup from the manufacturer(s) in original on manufacturer's letter head against the quality of the tendered item(s) as specified in the tender.

B.4 Copies of API Spec 7K certificates of the OEM(s) of their quoted product in line with para A.1 above.

B.5 Documentary evidence in respect of manufacturing and supply experience as specified under para A.2 & A.2.1, if applicable or A.7 from the concerned manufacturer(s) (having supplied such items either by manufacturer themselves or through their sole selling agent / distributor / dealer / supply house) along with the techno-commercial bid.

B.6 Documentary evidence in respect of bidder's own supply experience of supplying minimum 50% quantity (to be rounded to next higher whole figure) against each of the tendered item, of same or higher capacity and same or higher sizes, for which the bidder has quoted to any E&P companies/Drilling Contractors/Drilling service providers in the last 5 (five) years as on original bid closing date of the tender. Documentary evidence in respect of supplying the above mentioned items should be submitted with the technical bid, in the form of copies of relevant signed Purchase Orders along with copies of any of the following documents in respect of satisfactory execution of each of those Purchase Orders failing which the bids will be rejected:

- (i) Signed and sealed Satisfactory supply / completion report (in original on user's letter head) (OR)
- (ii) Bill of Lading (OR)
- (iii) Consignee delivery receipt / challan (OR)
- (iv) Central Excise Gate Pass / Tax Invoice issued under relevant rules of Central Excise / Vat / GST (OR)
- (v) Commercial Invoice / Payment Invoice

Note:

1) The Purchase Order date need not be within 5 (five) years preceding original bid closing date of this tender. However, the execution of supply should be within 5 (five) years preceding original bid closing date of this tender.

II) Original Bid Closing Date shall be considered by OIL for evaluation of BRC Criteria in case of any extension of the original bid closing date.

III) Satisfactory supply / completion report should be issued on company's letterhead with signature and stamp. Originals to be produced for verification on demand of OIL.

IV) In case the bidder submits the same Purchase Order(s) and relevant documents for supplementing the supply experience for both itself and the OEM(s), then the following additional documents are also to be submitted for supplementing the execution of supply from the OEM to the bidder as indicated in the submitted Purchase Order (s) failing which the bid will be rejected:

a) Copies of Purchase Order / Contract between the Bidder and the OEM and any of the following documents:

i) Commercial Invoice / Payment invoice of the OEM (OR)

ii) Bill of Lading (OR)

iii) Central Excise Gate Pass/Tax invoice issued under relevant rules of Central Excise /VAT/GST

B.7 Bidder should categorically confirm in the technical bid a delivery schedule within eight (08) months, FOB Port of dispatch, after establishment of letter of credit (in case of foreign bidder) or for dispatch of the equipment within eight (08) months after receipt of formal order (in case of indigenous bidder) failing which their offer will be rejected.

B.8 If the bidder is sole selling agent / distributor / dealer / supply house of any manufacturer(s) and have successfully supplied eighteen (18) numbers of Hand Slips for drill pipes of any sizes, twelve (12) numbers of Hand Slips for drill collars of any sizes and fourteen (14) numbers of Hand Slips for casings of any sizes to OIL in the last 05 (five) years as on original bid closing date and whose past performance has been satisfactory, the bidder need not satisfy Clause B.6. In this situation the bidder shall have to indicate the Purchase Order (P.O.) No. of OIL in their technical bid. However, this exemption shall be applicable only if the bidder has declared in the bid that they will be supplying the Rotary Slips from the same manufacturer(s) as per the last order supply.

B.9 The sole selling agent / distributor / dealer / supply house of any Original Equipment manufacturers should quote for the supply of Rotary Slips from those manufacturers who also meet the criteria as mentioned at clauses A.3, A.4 & A.5 above. The bidder is required to submit documentary evidence in respect of the above from the concerned manufacturer along with the techno-commercial bid.

BB. FINANCIAL:

1.0 **Annual Turnover:** The bidder shall have an annual financial turnover of minimum **US\$ 2,33,594 OR INR 163.47 Lacs** during any of the preceding 03 (three) financial years reckoned from the original bid closing date.

2.0 "Net Worth" of the bidder should be positive for the financial/accounting year just preceding to the original bid closing date of the tender (i.e. FY 2018-19).

3.0 Considering the time required for preparation of Financial Statements, if the last date of preceding financial / accounting year falls within the preceding six months reckoned from the original bid closing date and the Financial Statements of the

preceding financial / accounting year are not available with the bidder, then the financial turnover of the previous three financial / accounting years excluding the preceding financial / accounting year will be considered. In such cases, the Net worth of the previous financial / accounting year excluding the preceding financial / accounting year will be considered. **However, the bidder has to submit an affidavit/undertaking certifying that 'the balance sheet/Financial Statements for the financial year 2018-19 has actually not been audited so far'.**

Note:

a) For proof of Annual Turnover & Net worth any one of the following document must be submitted along with the bid:-

i) Audited Balance Sheet alongwith Profit & Loss account. In case of Foreign bidders, self-attested/digitally signed printed published accounts are also acceptable.

OR

ii) A certificate issued by a practicing Chartered/Cost Accountant (with Membership Number and Firm Registration Number), certifying the Annual turnover & Net worth as per format prescribed in ANNEXURE-D.

b) In case the bidder is a Central Govt. Organization/PSU/State Govt. Organization/Semi-State Govt. Organization or any other Central/State Govt. Undertaking, where the auditor is appointed only after the approval of Comptroller and Auditor General of India and the Central Government, their certificates may be accepted even though FRN is not available. However, bidder to provide documentary evidence for the same.

4.0 In case the Audited Balance Sheet and Profit & Loss Account submitted along with the bid are in currencies other than INR or US\$, the bidder shall have to convert the figures in equivalent INR or US\$ considering the prevailing conversion rate on the date of Balance Sheet and Profit & Loss Account. A CA certificate is to be submitted by the bidder regarding converted figures in equivalent INR or US\$.

CC. COMMERCIAL:

Commercial Bid Rejection Criteria will be as per Section D of General Terms & Conditions of Global Tender (MM/GLOBAL/E-01/2005) with following Special Bid Rejection Criteria.

1.0 Bids are invited under **Single Stage Two Bid System**. Bidders shall quote accordingly under Single Stage Two Bid System. **Please note that no price details should be furnished in the Technical (i.e. Unpriced) bid.** The "Unpriced Bid" shall contain all techno-commercial details except the prices, which shall be kept blank. The "Price Bid" containing the price schedule and the bidder's commercial terms and conditions must be uploaded separately as designated in e-portal. Bidder not complying with above submission procedure will be rejected.

2.0 The prices offered in the Price bid shall have to be firm through delivery and not subject to variation on any account. A bid submitted with an adjustable price shall be treated as non-responsive and rejected.

- 3.0 Bids received in physical form against online invitation through e-portal shall be rejected (except the documents specifically called for in hard copies, if any). Similarly, Bids received after the bid closing date and time shall be rejected. Also, modifications to bids received after the bid closing date & time shall not be considered.
- 4.0 Bids containing incorrect statement shall be rejected.
- 5.0 Validity of the bid shall be **minimum 120 days** from the date of actual Bid Closing Date. Bids with lesser validity will be straightway rejected.
- 6.0 **Bid security of INR 6,53,900.00 OR US\$ 9,344.00;** shall be furnished as a part of the TECHNICAL BID. **Any bid not accompanied by a proper bid security in ORIGINAL will be rejected without any further consideration.** A bid shall be rejected straightway if Original Bid Security is not received in hard copy within the stipulated date & time mentioned in the Tender and/or if the Bid Security validity is shorter than the validity indicated in Tender and/or if the Bid Security amount is lesser than the amount indicated in the Tender.
- 6.1 For exemption from submission of Bid Security, please refer Clause No. 9.8 (Section A) of “General Terms & Conditions” for e-Procurement as per Booklet No. MM/GLOBAL/E-01/2005 for E-procurement (ICB Tenders).
- 6.2 Bank Guarantee towards Bid Security shall remain valid up to **06.06.2020**.
- 7.0 Bidders must confirm that Goods, materials or plant(s) to be supplied shall be new, of recent make and of the best quality, workmanship & manufacture, shall be in full conformity with ordered specifications and shall be guaranteed for a period of 18 months from the date of shipment/dispatch or twelve (12) months from the date of receipt of the items at destination, whichever is earlier against any defects arising from faulty materials, workmanship or design. Defective goods/materials or parts rejected by OIL shall be replaced immediately by the supplier at the supplier’s expenses at no extra cost to OIL. This guarantee shall survive and hold good notwithstanding inspection, payment for and acceptance of the goods.
- 8.0 Successful bidder shall be required to furnish a Performance Security equivalent to ten (10%) of total evaluated value of Order, which should remain valid throughout the period of execution, including extension, if any and the entire warranty period in line with tender requirement. The successful bidder shall submit Performance Security within 30 days of award, failing which OIL reserves the right to cancel the order and forfeit their Bid Security. Bidders should undertake in their bids to submit Performance Security as stated above.
- 9.0 Offers should be submitted along with Integrity Pact duly signed online by the authorized signatory of the bidder, who signs the Bid. If any bidder refuses to sign Integrity Pact or declined to submit Integrity Pact with the offer, their bid shall be rejected straightway.
- 10.0 All the tendered items shall be evaluated individually; hence bidders are requested to quote accordingly.
- 11.0 Bidders are required to submit the summary of the prices in their price bids as per bid format (Summary), given below:

(i) **Price Bid Format (SUMMARY) for Foreign Bidders :**

SL. No.	Cost Details (Please indicate 'quoted currency')	Item No. 10	Item No. 20	Item No. 30	Item No. 40	Item No. 50	Item No. 60	Item No. 70	Item No. 80	Item No. 90	Item No. 100	Item No. 110	Item No. 120	Item No. 130	Item No. 140	Item No. 150	Item No. 160
(A)	Unit Material Cost:																
(B)	Quantity in Numbers:	4	6	4	6	5	6	10	4	6	7	6	4	3	2	8	6
(C)	Total Cost(Ax B):																
(D)	Total Packing & FOB Charges:																
(E)	Total FOB Port of Shipment value, (C + D):																
(F)	Total Ocean Freight Charges up to Kolkata, India:																
(G)	Banking & Insurance Charges @ 1.5% on Total FOB Value vide (E) above:																
(H)	Total CIF Kolkata value, (E + F + G):																
(I)	IGST @ 5% on (H):																
(J)	Compensatory Cess on (I), If any:																
(K)	Total CIF + IGST Value (H + I + J)																
(L)	Grand Total value in words:																
(M)	Gross Weight :																
(N)	Gross Volume :																

(ii) Price Bid Format (SUMMARY) for Indigenous Bidders :

SL. No.	Cost Details (Please indicate 'quoted currency')	Item No. 10	Item No. 20	Item No. 30	Item No. 40	Item No. 50	Item No. 60	Item No. 70	Item No. 80	Item No. 90	Item No. 100	Item No. 110	Item No. 120	Item No. 130	Item No. 140	Item No. 150	Item No. 160
(A)	Unit Material Cost:																
(B)	Quantity in Numbers:	4	6	4	6	5	6	10	4	6	7	6	4	3	2	8	6
(C)	Total Cost(Ax B):																
(D)	Total Packing and Forwarding Charges:																
(E)	Total Ex-works value, (C + D) :																
(F)	GST @ 5% on (E) above:																
(G)	Compensatory Cess, If any on (F):																
(H)	Total FOR Despatching Station value, (E + F + G):																
(I)	Total Inland Freight Charges upto Duliajan, Assam including GST:																
(J)	GST included Transit Insurance Charges @ 0.5 % of (H):																
(K)	Total FOR Duliajan value, (H + I + J) :																
(L)	Grand Total value in words::																
(M)	Gross Weight :																
(N)	Gross Volume :																
(O)	Import Content, if any:																

Note : i) Please indicate HSN Code of the quoted material. Cost of individual items must be shown separately as called in the Price Bid Format (SUMMARY), above.

ii) Domestic Bidders must quote inland freight charges upto Duliajan. In case bidder fails to quote inland freight charges, highest freight quoted by domestic bidder (considering pro-rata distance) against this tender or OIL's estimated freight, whichever is higher, shall be loaded to their offer for comparison purpose.

iii) The items covered under this enquiry shall be used by OIL in the PEL/ML areas and hence, applicable customs duty for import of goods shall be nil as per prevailing govt. policy. However, IGST @5% shall be applicable during import.

IGST /Concessional GST @5% shall be applicable for Indigenous bidders also. Indigenous bidders must quote Deemed Export prices. OIL will issue Project Authority Certificate (PAC) under Deemed Export benefit, where import content is declared by the bidder for availing Advance Licence for intermediate Supply. However, Indian bidders will not be issued Recommendatory Letter towards import, but EC will be provided by OIL for concessional GST @5% on the finished product.

12.0 Bidder shall accept and comply with the following clauses as given in the Bid Document, failing which bid shall be liable for rejection:

- i) Liquidated Damages
- ii) Warranty/Guarantee of material
- iii) Arbitration / Resolution of Dispute
- iv) Force Majeure
- v) Applicable Laws

(II) BID EVALUATION CRITERIA (BEC)

The bids conforming to the specifications, terms and conditions stipulated in the enquiry and considered to be responsive after subjecting to the Bid Rejection Criteria shall be considered for further evaluation as per General Terms and Conditions for Global Tender and the Bid Evaluation Criteria given below:

- 1.0 The evaluation of bids shall be done as per the Price Bid Format (SUMMARY) provided under (I), (C), BRC Commercial Para 11.0 and detailed below.
- 2.0 If there is any discrepancy between the unit price and the total price, the unit price will prevail and the total price shall be corrected. Similarly, if there is any discrepancy between words and figure, the amounts in words shall prevail and will be adopted for evaluation.
- 3.0 For conversion of foreign currency into Indian currency, B.C. selling (Market) rate declared by State Bank of India, one day prior to the date of price bid opening shall be considered. However, if the time lag between the opening of the bids and final decision exceed 3(three) months, then B.C. Selling(Market) rate of exchange declared by SBI on the date prior to the date of final decision shall be adopted for conversion and evaluation.

4.0 To ascertain the inter-se-ranking, bid prices shall be converted into Indian Rupees and the comparison of responsive bids shall be made as under, subject to corrections / adjustments, if any.

4.1 When only foreign bidders are involved:

Comparison of bids will be done on the basis of "TOTAL VALUE" as mentioned in para **11.0, (i), (K) of BRC Commercial** above.

NOTE: *Banking charge in the country of the foreign bidder shall be borne by the bidder. Banking charge 1% for payment through Letter of Credit. If confirmed L/C at buyer's account is required, 1.5 % will be loaded.

4.2 When only domestic bidders are involved:

Comparison of bids will be done on the basis of "TOTAL VALUE" as mentioned in para **11.0, (ii), (K) of BRC Commercial** above.

4.3 When both foreign and domestic bidders are involved:

The Grand Total Value of domestic bidder **as per para 11.0, (ii), (K) of BRC Commercial excluding (I+J) i.e** Grand Total Value of domestic bidder excluding inland transportation charges including GST and Insurance charges including GST worked out as above and Grand Total Value of the foreign bidder worked out **as per para 11.0, (i), (K) of BRC Commercial** will be compared.

Note: When more than one domestic bidders fall within price preference range, inter-se-ranking will be done on Grand Total Value basis. If the Government of India revises these evaluation criteria the same as applicable on the bid closing date will be adopted for evaluation of the offers.

5.0 Other terms and conditions of the enquiry shall be as per General Terms and Conditions for Global Tender. However, if any of the Clauses of the BEC/BRC mentioned here contradicts the Clauses in the General Terms & Conditions of Global Tender of the tender and/or elsewhere, those mentioned in this BEC/BRC shall prevail.

COMMERCIAL CHECK LIST

THE CHECK LIST MUST BE COMPLETED AND RETURNED WITH YOUR OFFER. PLEASE ENSURE THAT ALL THESE POINTS ARE COVERED IN YOUR OFFER. THESE WILL ENSURE THAT YOUR OFFER IS PROPERLY EVALUATED. PLEASE SELECT "Yes" OR "No" TO THE FOLLOWING QUESTIONS, IN THE RIGHT HAND COLUMN.

Sl#	REQUIREMENT	COMPLIANCE
1.0	Whether bid submitted under Single Stage Two Bid System?	Yes / No
2.0	Whether quoted as manufacturer?	Yes / No
2.1	Whether quoted as OEM Dealer / Supply House. To Specify-	Yes / No
2.2	If quoted as OEM Dealer / Supply House	Yes / No
	(a) Whether submitted valid and proper authorization letter from manufacturer confirming that bidder is their authorized Dealer / supply House for the product offered ?	
	(b) Whether manufacturer's back-up Warranty/Guarantee certificate submitted?	
3.0	Whether ORIGINAL Bid Bond (not copy of Bid Bond) as per Revised Format Sent separately? If YES, provide details	Yes / No
	(a) Amount :	
	(b) Name of issuing Bank :	
	(c) Validity of Bid Bond :	
4.0	Whether offered firm prices ?	Yes / No
4.1	Whether quoted offer validity of 120 days from the bid closing date of tender?	Yes / No
4.2	Whether quoted a firm delivery period?	Yes / No
4.3	Whether agreed to the NIT Warranty clause?	Yes / No
4.4	Whether confirmed acceptance of NIT Payment Terms	Yes / No
5.0	Whether confirmed to submit PBG as asked for in NIT?	Yes / No
5.1	Whether agreed to submit PBG within 30 days of placement of order?	Yes / No
6.0	Whether Price submitted as per Price Schedule of the tender?	Yes / No
7.0	Whether quoted as per NIT (without any deviations)?	Yes / No
7.0	Whether quoted any deviation?	Yes / No
7.1	Whether deviation separately highlighted?	Yes / No
8.0	Whether indicated the country of origin for the items quoted?	Yes / No
8.1	Whether technical literature / catalogue enclosed?	Yes / No
8.2	Whether weight & volume of items offered indicated?	Yes / No
9.0	For Foreign Bidders - Whether offered FOB / FCA port of despatch including sea / air worthy packing & forwarding?	Yes / No
9.1	For Foreign Bidders – Whether port of shipment indicated. To specify:	Yes / No
9.2	For Foreign Bidders only - Whether indicated ocean freight up to Kolkata port (Excluding marine insurance) ?	Yes / No
9.3	Whether Indian Agent applicable ?	Yes / No
	If YES, whether following details of Indian Agent provided?	
	(a) Name & address of the agent in India – To indicate	
	(b) Amount of agency commission – To indicate	
	(c) Whether agency commission included in quoted material value?	

10.0	For Indian Bidders – Whether indicated the place from where the goods will be dispatched. To specify :	Yes / No
10.1	For Indian Bidders – Whether road transportation charges up to Duliajan quoted?	Yes / No
10.2	For Indian Bidders only - Whether offered Ex-works price including packing/forwarding charges?	Yes / No
10.3	For Indian Bidders only - Whether indicated import content in the offer?	Yes / No
10.4	For Indian Bidders only - Whether offered Deemed Export prices?	Yes / No
10.5	For Indian Bidders only – Whether all applicable Taxes & Duties have been quoted?	Yes / No
11.0	Whether all BRC/BEC clauses accepted ?	Yes / No
12.0	Whether Integrity Pact with digital signature uploaded?	Yes / No
12.1	Whether all the clauses in the Integrity Pact have been accepted?	Yes / No
12.2	Whether all Financial documents as per BRC Financial have been uploaded?	Yes / No

TECHNICAL CHECK LIST

Sl. No	DESCRIPTIONS	REMARKS
1	Whether quoted the item as manufacturer	YES / NO
2	Whether quoted the item as sole selling agent / distributor / dealer / supply house of any manufacturer,	YES / NO
3	Whether the offered hand slips are as per the tender specifications & features in all respect?	YES / NO
4	Whether the offered items are brand new, unused, free from any kind of defect and of prime quality?	YES / NO
5	Whether copies of API Spec 7K certificate enclosed with the quotation?	YES / NO
6	Whether name of manufacturer & country of origin indicated?	YES / NO
7	Whether authorisation certificate from manufacturer with warranty support provided if the bidder is not a manufacturer?	YES / NO
8	Whether relevant Catalogue, Drawings, Literatures etc in English language (US or UK) enclosed with the quotation?	YES / NO
9	Whether documentary evidence of previous orders & performance report enclosed as desired vide Notes of the NIT.	YES / NO
10	Whether warranty would be for 18 months from date of receipt or 12 months from date of receipt of the items?	YES / NO
11	Whether the defective item/ parts, if any, rejected by us will be replaced by you free of cost?	YES / NO
12	Any deviation from NIT?	YES / NO

Signature _____

Name _____

Designation _____

CERTIFICATE OF ANNUAL TURNOVER & NET WORTH

TO BE ISSUED BY PRACTISING **CHARTARD ACCOUNTANTS' FIRM** ON THEIR LETTER HEAD

TO WHOM IT MAY CONCERN

This is to certify that the following financial positions extracted from the audited financial statements of M/s.....(Name of the bidder) for the last three (3) completed accounting years upto..... **(as the case may be)** are correct

YEAR	TURN OVER In INR (Rs.) Crores/ US \$ Million) *	NET WORTH In INR (Rs.) Crores / US \$ Million) *

*Rate of conversion (if used any): USD 1.00 = INR

Place:

Date:

Seal

Membership No:

Registration Code:

Signature

***Applicable only for GLOBAL tenders**

**Format of undertaking by Bidders towards submission of authentic information/documents
(To be typed on the letter head of the bidder)**

Ref. No _____

Date _____

Sub: Undertaking of authenticity of information/documents submitted

Ref: Your tender No. _____ Dated _____

To,
The HOD-Materials
Materials Deptt,
OIL, Duliajan

Sir,

With reference to our quotation against your above-referred tender, we hereby undertake that no fraudulent information/documents have been submitted by us.

We take full responsibility for the submission of authentic information/documents against the above cited bid.

We also agree that, during any stage of the tender/contract agreement, in case any of the information/documents submitted by us are found to be false/forged/fraudulent, OIL has right to reject our bid at any stage including forfeiture of our EMD and/or PBG and/or cancel the award of contract and/or carry out any other penal action on us, as deemed fit.

Yours faithfully,
For (type name of the firm here)

Signature of Authorised Signatory

Name :

Designation :

Phone No.

Place :

Date :

(Affix Seal of the Organization here, if applicable)

-----*****-----

**TECHNICAL EVALUATION MATRIX
(TO BE FILLED IN BY BIDDER DULY SIGNED)**

TECHNICAL SPECIFICATIONS

Clause Number	DESCRIPTION	BIDDER’S RESPONSE (Complied / Not Complied / Deviation / Not Applicable)	TO BE FILLED BY THE BIDDER Relevant Location of their Bid to support the remarks / compliance (Reference of Document name / Serial number / Page number of bid for documentary evidence)
Clause A (Item Number 10)	<p>HAND SLIP FOR 2.3/8 INCHES OD DRILL PIPE - 04 (FOUR) NUMBERS</p> <p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p> <ol style="list-style-type: none"> 1) Rotary hand slip 88.90 mm (3.1/2 inches) Body complete with Elastomer Flex handles & inserts for 60.325 mm (2.3/8 inches) OD drill pipe. Hand slip should have an API taper of 4 inch/ft. & suitable for use in 17.1/2 inches Square drive Rotary Table. 2) Minimum Load bearing capacity of the Rotary Hand Slip should be not less than 150 Ton. 3) The supporting slips should have minimum 11 inches (279.40 mm) gripping length. 4) The slips should be manufactured from high quality alloy steel; fully heat treated and should strictly conform to API 7K (latest edition). 		

	<p>5) Mass Slip weight i.e. weight of the complete slip with inserts and handles should be within 150 pounds (Maximum)</p> <p>6) Extra set of Inserts for each slip - 2 Set (Total 8 Sets).</p> <p>7) Extra Elastomer Flex Handle for each slip - 2 Numbers (Total 8 Nos).</p>		
<p>Clause B (Item Number 10)</p>	<p>SPECIAL REQUIREMENTS:</p> <p>1) SR-1 Proof Load Test: The items (HAND SLIP FOR 2.3/8 INCHES OD DRILL PIPE) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K – Annex A.2). Test reports should be submitted along with the supply.</p> <p>2) SR-3 Data Book: The Manufacturer’s Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply.</p>		
<p>Clause A (Item Number 20)</p>	<p>HAND SLIP FOR 2.7/8 INCHES OD DRILL PIPE - 06 (SIX) NUMBERS</p> <p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p> <p>1) Rotary hand slip 88.90 mm (3.1/2 inches) Body complete with Elastomer Flex handles & inserts for 73.025 mm (2.7/8 inches) OD drill pipe. Hand slip should have an API taper of 4 inch/ft. & suitable for use in 17.1/2 inches Square drive Rotary Table.</p> <p>2) Minimum Load bearing capacity of the Rotary Hand Slip should be not less than 150 Ton.</p> <p>3) The supporting slips should have minimum 11 inches (279.40 mm) gripping length.</p> <p>4) The slips should be manufactured from high quality alloy</p>		

	<p>steel; fully heat treated and should strictly conform to API 7K (latest edition).</p> <p>5) Mass Slip weight i.e. weight of the complete slip with inserts and handles should be within 150 pounds (Maximum)</p> <p>6) Extra set of Inserts for each slip - 2 Set (Total 12 Sets).</p> <p>7) Extra Elastomer Flex Handle for each slip - 2 Numbers (Total 12 Nos).</p>		
<p>Clause B (Item Number 20)</p>	<p>SPECIAL REQUIREMENTS:</p> <p>1) SR-1 Proof Load Test: The items (HAND SLIP FOR 2.7/8 INCHES OD DRILL PIPE) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K – Annex A.2). Test reports should be submitted along with the supply.</p> <p>2) SR-3 Data Book: The Manufacturer’s Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply.</p>		
<p>Clause A (Item Number 30)</p>	<p>HAND SLIP FOR 4.1/2 INCHES OD DRILL PIPE - 04 (FOUR) NUMBERS</p> <p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p> <p>1) Rotary hand slip 127.00 mm (5 inches) Body complete with Elastomer Flex handles & inserts for 114.30 mm (4.1/2 inches) OD drill pipe. Hand slip should have an API taper of 4 inch/ft. & suitable for use in 27.1/2 inches Square drive Rotary Table.</p> <p>2) Minimum Load bearing capacity of the Rotary Hand Slip should be not less than 350 Ton.</p> <p>3) The supporting slips should have minimum 13.3/4 inches (349.25 mm) gripping length.</p>		

	<p>4) The slips should be manufactured from high quality alloy steel; fully heat treated and should strictly conform to API 7K (latest edition).</p> <p>5) Mass Slip weight i.e. weight of the complete slip with inserts and handles should be within 200 pounds (Maximum)</p> <p>6) Extra set of Inserts for each slip - 2 Set (Total 8 Sets).</p> <p>7) Extra Elastomer Flex Handle for each slip - 2 Numbers (Total 8 Nos).</p>		
<p>Clause B (Item Number 30)</p>	<p>SPECIAL REQUIREMENTS:</p> <p>1) SR-1 Proof Load Test: The items (HAND SLIP FOR 4.1/2 INCHES OD DRILL PIPE) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K – Annex A.2). Test reports should be submitted along with the supply.</p> <p>2) SR-3 Data Book: The Manufacturer’s Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply.</p>		
<p>Clause A (Item Number 40)</p>	<p>HAND SLIP FOR 5 INCHES OD DRILL PIPE - 06 (SIX) NUMBERS</p> <p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p> <p>1) Rotary hand slip 127.00 mm (5 inches) Body complete with Elastomer Flex handles & inserts for 127.00 mm (5 inches) OD drill pipe. Hand slip should have an API taper of 4 inch/ft. & suitable for use in 27.1/2 inches Square drive Rotary Table.</p> <p>2) Minimum Load bearing capacity of the Rotary Hand Slip should be not less than 350 Ton.</p>		

	<p>3) The supporting slips should have minimum 13.3/4 inches (349.25 mm) gripping length.</p> <p>4) The slips should be manufactured from high quality alloy steel; fully heat treated and should strictly conform to API 7K (latest edition).</p> <p>5) Mass Slip weight i.e. weight of the complete slip with inserts and handles should be within 200 pounds (Maximum)</p> <p>6) Extra set of Inserts for each slip - 2 Set (Total 12 Sets).</p> <p>7) Extra Elastomer Flex Handle for each slip - 2 Numbers (Total 12 Nos).</p>		
<p>Clause B (Item Number 40)</p>	<p>SPECIAL REQUIREMENTS:</p> <p>1) SR-1 Proof Load Test: The items (HAND SLIP FOR 5 INCHES OD DRILL PIPE) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K – Annex A.2). Test reports should be submitted along with the supply.</p> <p>2) SR-3 Data Book: The Manufacturer’s Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply.</p>		
<p>Clause A (Item Number 50)</p>	<p>HAND SLIP FOR 8 INCHES OD DRILL COLLAR - 05 (FIVE) NUMBERS</p> <p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p> <p>1) Multi-segment Forged Drill Collar Rotary Hand Slip for 8 inches OD Drill Collars complete with Circular Buttons and handles. Hand slip should have an API taper of 4 inch/ft. & suitable for use in 27.1/2" Square drive Rotary Table.</p> <p>2) Minimum Load bearing capacity of the Rotary Hand Slip</p>		

	<p>should be not less than 150 Ton.</p> <p>3) The supporting slips should have minimum 9 inches (228.60 mm) gripping length.</p> <p>4) The slips should be manufactured from high quality alloy steel; fully heat treated and should strictly conform to API 7K (latest edition).</p> <p>5) The handles should be flexible type and centre handle to be provided for better handling of the equipment.</p> <p>6) Mass Slip weight i.e. weight of the complete slip with inserts and handles should be within 200 pounds (Maximum)</p> <p>7) Extra Set of Circular Buttons for each slip - 2 Set (Total 10 Sets).</p> <p>8) Extra Elastomer Flex Handle for each slip - 2 Numbers (Total 10 Nos).</p>		
<p>Clause B (Item Number 50)</p>	<p>SPECIAL REQUIREMENTS:</p> <p>1) SR-1 Proof Load Test: The items (HAND SLIP FOR 8 INCHES OD DRILL COLLAR) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K – Annex A.2). Test reports should be submitted along with the supply.</p> <p>2) SR-3 Data Book: The Manufacturer’s Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply.</p>		
<p>Clause A (Item Number 60)</p>	<p>HAND SLIP FOR 9.1/2 INCHES OD DRILL COLLAR - 06 (SIX) NUMBERS</p> <p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p>		

	<p>1) Multi-segment Forged Drill Collar Rotary Hand Slip for 9.1/2 inches OD Drill Collars complete with Circular Buttons and handles. Hand slip should have an API taper of 4 inch/ft. & suitable for use in 27.1/2" Square drive Rotary Table.</p> <p>2) Minimum Load bearing capacity of the Rotary Hand Slip should be not less than 150 Ton.</p> <p>3) The supporting slips should have minimum 9 inches (228.60 mm) gripping length.</p> <p>4) The slips should be manufactured from high quality alloy steel; fully heat treated and should strictly conform to API 7K (latest edition).</p> <p>5) The handles should be flexible type and centre handle to be provided for better handling of the equipment.</p> <p>6) Mass Slip weight i.e. weight of the complete slip with inserts and handles should be within 200 pounds (Maximum)</p> <p>7) Extra Set of Circular Buttons for each slip - 2 Set (Total 12 Sets).</p> <p>8) Extra Elastomer Flex Handle for each slip - 2 Numbers (Total 12 Nos).</p>		
<p>Clause B (Item Number 60)</p>	<p>SPECIAL REQUIREMENTS:</p> <p>1) SR-1 Proof Load Test: The items (HAND SLIP FOR 9.1/2 INCHES OD DRILL COLLAR) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K – Annex A.2). Test reports should be submitted along with the supply.</p> <p>2) SR-3 Data Book: The Manufacturer’s Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply.</p>		
<p>Clause</p>	<p>HAND SLIP FOR 2.7/8 INCHES OD EU TUBING - 10 (TEN)</p>		

<p>A (Item Number 70)</p>	<p>NUMBERS</p> <p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p> <ol style="list-style-type: none"> 1) Rotary hand slip 88.90 mm (3.1/2 inches) Body complete with Elastomer Flex handles & inserts for 73.025 mm (2.7/8 inches) OD EU tubing. Hand slip should have an API taper of 4 inch/ft. & suitable for use in 27.1/2 inches Square drive Rotary Table. 2) Minimum Load bearing capacity of the Rotary Hand Slip should be not less than 150 Ton. 3) The supporting slips should have minimum 11 inches (279.40 mm) gripping length. 4) The slips should be manufactured from high quality alloy steel; fully heat treated and should strictly conform to API 7K (latest edition). 5) Mass Slip weight i.e. weight of the complete slip with inserts and handles should be within 150 pounds (Maximum) 6) Extra set of Inserts for each slip - 2 Set (Total 20 Sets). 7) Extra Elastomer Flex Handle for each slip - 2 Numbers (Total 20 Nos). 		
<p>Clause B (Item Number 70)</p>	<p>SPECIAL REQUIREMENTS:</p> <ol style="list-style-type: none"> 1) SR-1 Proof Load Test: The items (HAND SLIP FOR 2.7/8 INCHES OD EU TUBING) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K – Annex A.2). Test reports should be submitted along with the supply. 2) SR-3 Data Book: The Manufacturer’s Data Book as per API 		

	Specification 7K – Annex A.5 for all of the items should be submitted along with the supply.		
Clause A (Item Number 80)	<p>HAND SLIP FOR 20 INCHES OD CASING – 04 (FOUR) NUMBERS</p> <p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p> <ol style="list-style-type: none"> 1) Extra long Casing hand slips complete with handles & circular buttons for 508 mm (20 inches) OD casing pipes. Hand slip should have an API taper of 4 inch/ft. 2) Extra set of circular buttons for each slip - 1 set (Total 04 sets) 3) Minimum load bearing capacity of the casing hand slips should not be less than 250 tons. 4) The supporting slips should have minimum 13 inches (330.20 mm) gripping length and should provide maximum circumferential grip for uniform pressure around the casing. 5) The handles should be flexible type and centre handle to be provided for better handling of the equipment. 		
Clause B (Item Number 80)	<p>SPECIAL REQUIREMENTS:</p> <ol style="list-style-type: none"> 1) SR-1 Proof Load Test: The items (HAND SLIP FOR 20 INCHES OD CASING) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K – Annex A.2). Test reports should be submitted along with the supply. 2) SR-3 Data Book: The Manufacturer’s Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply. 		
Clause A (Item	HAND SLIP FOR 13.3/8 INCHES OD CASING – 06 (SIX) NUMBERS		

Number 90)	<p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p> <ol style="list-style-type: none"> 1) Extra long Casing hand slips complete with handles & circular buttons for 339.725 mm (13.3/8 inches) OD casing pipes. Hand slip should have an API taper of 4 inch/ft. 2) Extra set of circular buttons for each slip - 1 set (Total 06 sets) 3) Minimum load bearing capacity of the casing slips should not be less than 450 Tons. 4) The supporting slips should have minimum 13 inches (330.20 mm) gripping length and should provide maximum circumferential grip for uniform pressure around the casing. 5) The handles should be flexible type and centre handle to be provided for better handling of the equipment. 		
Clause B (Item Number 90)	<p>SPECIAL REQUIREMENTS:</p> <ol style="list-style-type: none"> 1) SR-1 Proof Load Test: The items (HAND SLIP FOR 13.3/8 INCHES OD CASING) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K – Annex A.2). Test reports should be submitted along with the supply. 2) SR-3 Data Book: The Manufacturer’s Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply. 		
Clause A (Item Number 100)	<p>HAND SLIP FOR 9.5/8 INCHES OD CASING – 07 (SEVEN) NUMBERS</p> <p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p>		

	<p>1) Extra long Casing hand slips complete with handles & circular buttons for 244.475 mm (9.5/8 inches) OD casing pipes. Hand slip should have an API taper of 4 inch/ft.</p> <p>2) Extra set of circular buttons for each slip - 1 set (Total 07 sets)</p> <p>3) Minimum load bearing capacity of the casing slips should not be less than 450 Tons.</p> <p>4) The supporting slips should have minimum 13 inches (330.20 mm) gripping length and should provide maximum circumferential grip for uniform pressure around the casing.</p> <p>5) The handles should be flexible type and centre handle to be provided for better handling of the equipment.</p>		
<p>Clause B (Item Number 100)</p>	<p>SPECIAL REQUIREMENTS:</p> <p>1) SR-1 Proof Load Test: The items (HAND SLIP FOR 9.5/8 INCHES OD CASING) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K – Annex A.2). Test reports should be submitted along with the supply.</p> <p>2) SR-3 Data Book: The Manufacturer’s Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply.</p>		
<p>Clause A (Item Number 110)</p>	<p>HAND SLIP FOR 5.1/2 INCHES OD CASING – 06 (SIX) NUMBERS</p> <p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p> <p>1) Multi-segment Forged Rotary Hand Slip for 5.1/2 inches OD Casing complete with Circular Buttons and handles. Hand slip should have an API taper of 4 inch/ft. & suitable for use in</p>		

	<p>27.1/2" Square drive Rotary Table.</p> <p>2) Minimum Load bearing capacity of the Rotary Hand Slip should be not less than 150 Ton.</p> <p>3) The supporting slips should have minimum 9 inches (228.60 mm) gripping length.</p> <p>4) The slips should be manufactured from high quality alloy steel; fully heat treated and should strictly conform to API 7K (latest edition).</p> <p>5) The handles should be flexible type and centre handle to be provided for better handling of the equipment.</p> <p>6) Mass Slip weight i.e. weight of the complete slip with inserts and handles should be within 175 pounds (Maximum)</p> <p>7) Extra Set of Circular Buttons for each slip - 2 Set (Total 12 Sets).</p> <p>8) Extra Elastomer Flex Handle for each slip - 2 Numbers (Total 12 Nos).</p>		
<p>Clause B (Item Number 110)</p>	<p>SPECIAL REQUIREMENTS:</p> <p>1) SR-1 Proof Load Test: The items (HAND SLIP FOR 5.1/2 INCHES OD CASING) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K – Annex A.2). Test reports should be submitted along with the supply.</p> <p>2) SR-3 Data Book: The Manufacturer’s Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply.</p>		
<p>Clause A (Item Number 120)</p>	<p>HAND SLIP FOR 7 INCHES OD CASING – 04 (FOUR) NUMBERS</p> <p>Each Rotary hand slip should be manufactured and</p>		

	<p>monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p> <ol style="list-style-type: none"> 1) Extra long Casing hand slips complete with handles & circular buttons for 177.80 mm (7 inches) OD casing pipes. Hand slip should have an API taper of 4 inch/ft. 2) Extra set of circular buttons for each slip - 1 set (Total 04 sets) 3) Minimum load bearing capacity of the casing slips should not be less than 350 Tons. 4) The supporting slips should have minimum 13 inches (330.20 mm) gripping length and should provide maximum circumferential grip for uniform pressure around the casing. 5) The handles should be flexible type and centre handle to be provided for better handling of the equipment. 		
<p>Clause B (Item Number 120)</p>	<p>SPECIAL REQUIREMENTS:</p> <ol style="list-style-type: none"> 1) SR-1 Proof Load Test: The items (HAND SLIP FOR 7 INCHES OD CASING) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K – Annex A.2). Test reports should be submitted along with the supply. 2) SR-3 Data Book: The Manufacturer’s Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply. 		
<p>Clause A (Item Number 130)</p>	<p>HAND SLIP FOR 3.1/2 INCHES OD DRILL COLLAR - 03 (THREE) NUMBERS</p> <p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p> <ol style="list-style-type: none"> 1) Multi-segment Forged Drill Collar Rotary Hand Slip for 3.1/2 		

	<p>inches OD Drill Collars complete with Circular Buttons and handles. Hand slip should have an API taper of 4 inch/ft. & suitable for use in 27.1/2" Square drive Rotary Table.</p> <p>2) Minimum Load bearing capacity of the Rotary Hand Slip should be not less than 150 Ton.</p> <p>3) The supporting slips should have minimum 7.7/8 inches (200.025 mm) gripping length.</p> <p>4) The slips should be manufactured from high quality alloy steel; fully heat treated and should strictly conform to API 7K (latest edition).</p> <p>5) The handles should be flexible type and centre handle to be provided for better handling of the equipment.</p> <p>6) Mass Slip weight i.e. weight of the complete slip with inserts and handles should be within 125 pounds (Maximum)</p> <p>7) Extra Set of Circular Buttons for each slip - 2 Set (Total 6 Sets).</p> <p>8) Extra Elastomer Flex Handle for each slip - 2 Numbers (Total 6 Nos).</p>		
<p>Clause B (Item Number 130)</p>	<p>SPECIAL REQUIREMENTS:</p> <p>1) SR-1 Proof Load Test: The items (HAND SLIP FOR 3.1/2 INCHES OD DRILL COLLAR) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K – Annex A.2). Test reports should be submitted along with the supply.</p> <p>2) SR-3 Data Book: The Manufacturer’s Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply.</p>		
<p>Clause A (Item</p>	<p>HAND SLIP FOR 4.3/4 INCHES OD DRILL COLLAR - 02 (TWO) NUMBERS</p>		

<p>Number 140)</p>	<p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p> <ol style="list-style-type: none"> 1) Multi-segment Forged Drill Collar Rotary Hand Slip for 4.3/4 inches OD Drill Collars complete with Circular Buttons and handles. Hand slip should have an API taper of 4 inch/ft. & suitable for use in 27.1/2" Square drive Rotary Table. 2) Minimum Load bearing capacity of the Rotary Hand Slip should be not less than 150 Ton. 3) The supporting slips should have minimum 7.7/8 inches (200.025 mm) gripping length. 4) The slips should be manufactured from high quality alloy steel; fully heat treated and should strictly conform to API 7K (latest edition). 5) The handles should be flexible type and centre handle to be provided for better handling of the equipment. 6) Mass Slip weight i.e. weight of the complete slip with inserts and handles should be within 125 pounds (Maximum) 7) Extra Set of Circular Buttons for each slip - 2 Set (Total 4 Sets). 8) Extra Elastomer Flex Handle for each slip - 2 Numbers (Total 4 Nos). 		
<p>Clause B (Item Number 140)</p>	<p>SPECIAL REQUIREMENTS:</p> <ol style="list-style-type: none"> 1) SR-1 Proof Load Test: The items (HAND SLIP FOR 4.3/4 INCHES OD DRILL COLLAR) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K – Annex A.2). Test reports should be submitted along with the supply. 		

	2) SR-3 Data Book: The Manufacturer's Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply.		
Clause A (Item Number 150)	<p>HAND SLIP FOR 6.1/2 INCHES OD DRILL COLLAR - 08 (EIGHT) NUMBERS</p> <p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p> <ol style="list-style-type: none"> 1) Multi-segment Forged Drill Collar Rotary Hand Slip for 6.1/2 inches OD Drill Collars complete with Circular Buttons and handles. Hand slip should have an API taper of 4 inch/ft. & suitable for use in 27.1/2" Square drive Rotary Table. 2) Minimum Load bearing capacity of the Rotary Hand Slip should be not less than 150 Ton. 3) The supporting slips should have minimum 9 inches (228.60 mm) gripping length. 4) The slips should be manufactured from high quality alloy steel; fully heat treated and should strictly conform to API 7K (latest edition). 5) The handles should be flexible type and centre handle to be provided for better handling of the equipment. 6) Mass Slip weight i.e. weight of the complete slip with inserts and handles should be within 175 pounds (Maximum) 7) Extra Set of Circular Buttons for each slip - 2 Set (Total 16 Sets). 8) Extra Elastomer Flex Handle for each slip - 2 Numbers (Total 16 Nos). 		
Clause B (Item	SPECIAL REQUIREMENTS:		

<p>Number 150)</p>	<p>1) SR-1 Proof Load Test: The items (HAND SLIP FOR 6.1/2 INCHES OD DRILL COLLAR) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K – Annex A.2). Test reports should be submitted along with the supply.</p> <p>2) SR-3 Data Book: The Manufacturer’s Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply.</p>		
<p>Clause A (Item Number 160)</p>	<p>HAND SLIP FOR 3.1/2 INCHES OD DRILL PIPE - 06 (SIX) NUMBERS</p> <p>Each Rotary hand slip should be manufactured and monogrammed strictly as per API 7K (latest edition). Each Rotary hand slip should consist of, but not limited to:</p> <p>1) Rotary hand slip 114.30 mm (4.1/2 inches) Body complete with Elastomer Flex handles & inserts for 88.90 mm (3.1/2 inches) OD drill pipe. Hand slip should have an API taper of 4 inch/ft. & suitable for use in 27.1/2 inches Square drive Rotary Table.</p> <p>2) Minimum Load bearing capacity of the Rotary Hand Slip should be not less than 350 Ton.</p> <p>3) The supporting slips should have minimum 13.3/4 inches (349.25 mm) gripping length.</p> <p>4) The slips should be manufactured from high quality alloy steel; fully heat treated and should strictly conform to API 7K (latest edition).</p> <p>5) Mass Slip weight i.e. weight of the complete slip with inserts and handles should be within 210 pounds (Maximum)</p> <p>6) Extra set of Inserts for each slip - 2 Set (Total 12 Sets).</p> <p>7) Extra Elastomer Flex Handle for each slip - 2 Numbers (Total</p>		

	12 Nos).		
Clause B (Item Number 160)	<p>SPECIAL REQUIREMENTS:</p> <p>1) SR-1 Proof Load Test: The items (HAND SLIP FOR 3.1/2 INCHES OD DRILL PIPE) shall be given a proof load test and subsequently examined in accordance with 8.6 and should be marked "SR-1" accordingly near the load rating identification (API Specification 7K – Annex A.2). Test reports should be submitted along with the supply.</p> <p>2) SR-3 Data Book: The Manufacturer’s Data Book as per API Specification 7K – Annex A.5 for all of the items should be submitted along with the supply.</p>		
SPECIAL NOTES TO BIDDERS			
1	The items shall be brand new, unused & of prime quality. Bidder shall warrant (in the event of an order) that the product supplied will be free from all defects & fault in material, workmanship & manufacture and shall be in full conformity with API specification 7K standard (6th Edition). This clause shall be valid for 18 months from date of shipment/dispatch or 12 months from the date of receipt of the items whichever is earlier. The defective materials, if any, rejected by OIL shall be replaced by the supplier at their own arrangements. Bidders must confirm the same in their quotations.		
2	The bidder must specify the offered items in details, forwarding relevant product catalogue, literature, detailed drawings with exploded views of each & every item of the offered product with complete spare parts list & clearly indicating the various parts with part numbers.		
3	<p>The items are to be designed/manufactured/tested strictly as per API Spec 7K (Latest Edition) and bidders are required to forward valid API 7K specification certificate (having authorization for manufacturing of Rotary Slips) along with the quotation.</p> <p>Moreover copies of API 7K (having authorization for manufacturing of Rotary Slips) certificates of the manufacturer for the last 5 (Five) years (i.e. continuous without having any break in between), preceding the Original Bid Closing date of</p>		

	the tender, shall be submitted along with techno-commercial bid. Bids without copies of valid relevant API certificates or with break(s) in between will be rejected.		
4	Necessary testing and marking shall be done as per API Spec 7K (6th Edition), and as specified elsewhere in the tender. The items shall be die stamped with the manufacturer's name, the API monogram and the month and year of manufacture. Bidders are to confirm the same while quoting.		
5	Equipment should be fully radio graphed, ultrasonic tested, proof load tested & MPI. In the event of an order, all relevant testing documents and manufacturers' data book as per API should be submitted along with the delivery of the order. Bidder should confirm the same while quoting.		
6	Bidder should indicate the name of manufacturer, country of origin and port of dispatch of the materials.		
7	Any deviation(s) from the tender specification should be clearly highlighted specifying justification in support of deviation.		
8	Bidder should note that in the event of an order, the API licenses for manufacturing the Rotary Slips along with authorization for API monogramming should be valid, without any break, till execution of purchase order. Valid relevant API certificate to be submitted along with the supply. Bidder should categorically confirm compliance while quoting.		
9	Bidder to sign and submit completely filled up Technical Evaluation Matrix for Bid evaluation criteria and Technical specification.		
10	Bidder should categorically confirm in the technical bid a delivery schedule within eight (08) months, FOB Port of dispatch, after establishment of letter of credit (in case of foreign bidder) or for dispatch of the equipment within eight (08) months after receipt of formal order (in case of indigenous bidder) failing which their offer will be rejected.		

TECHNICAL EVALUATION MATRIX (TO BE FILLED IN BY BIDDER DULY SIGNED)			
BID EVALUATION CRITERIA			
Clause Number	DESCRIPTION	BIDDER'S RESPONSE (Complied / Not Complied / Deviation / Not Applicable)	TO BE FILLED BY THE BIDDER Relevant Location of their Bid to support the remarks / compliance (Reference of Document name / Serial number / Page number of bid for documentary evidence)
A.	<p>IN CASE THE BIDDER IS A MANUFACTURER:</p> <p>In case the bidder is a manufacturer of the offered item(s), then bidder must furnish the following documents along with the technical bid failing which the bids will be rejected:</p>		
A.1	<p>The bidder should have minimum 5 years continuous experience of manufacturing of Rotary Slips (Hand Slips for Drill Pipes, Tubings, Drill Collars and Casings) conforming to API spec. 7K certification. For this purpose, the period reckoned shall be period prior to the date of original bid closing date of the tender. Copies of API 7K certificates, having authorization for Rotary Slips, for the last 5 (Five) years (i.e. continuous without having any break in between) must be submitted along with techno - commercial bid. Bids without copies of valid API 7K certificates or with a break in between will be rejected.</p>		
A.2	<p>The bidder should have manufactured and supplied minimum 50% quantity (to be rounded to next higher whole figure) against each of the tendered item, of same or higher capacity and same or higher sizes, for which the bidder has quoted to any E&P companies/Drilling Contractors/Drilling service providers in the last 5 (five) years as on</p>		

	<p>original bid closing date of the tender (either by themselves or through their sole selling agent/distributor/dealer/supply house).</p> <p>Documentary evidence in respect of manufacturing and supplying the above mentioned items should be submitted with the technical bid, in the form of copies of relevant signed Purchase Orders along with copies of any of the following documents in respect of satisfactory execution of each of those Purchase Orders failing which the bids will be rejected:</p> <p>(i) Signed and sealed Satisfactory supply / completion report (in original on user's letter head) (OR) (ii) Bill of Lading (OR) (iii) Consignee delivery receipt / challan (OR) (iv) Central Excise Gate Pass / Tax Invoice issued under relevant rules of Central Excise / Vat / GST (OR) (v) Commercial Invoice / Payment Invoice</p> <p>Note:</p> <p>a) The Purchase Order date need not be within 5 (five) years preceding original bid closing date of this tender. However, the execution of supply should be within 5 (five) years preceding original bid closing date of this tender.</p> <p>b) Original Bid Closing Date shall be considered by OIL for evaluation of BRC Criteria in case of any extension of the original bid closing date.</p> <p>c) Satisfactory supply / completion report should be issued on company's letterhead with signature and stamp. Originals to be produced for verification on demand of OIL.</p>		
A.2.1	<p>In case, for supplementing manufacturer's supply experience criteria (A.2), the manufacturer submits Purchase Order(s) and relevant documents which is through their sole selling agent / distributor / dealer / supply house, then following additional documents are also to be submitted:</p>		

	<p>a) Copies of signed Purchase Order(s) / Contract agreement(s) between the manufacturer and the sole selling agent / distributor / dealer / supply house and copies of any of the following documents in respect of satisfactory execution of each of those Purchase Order(s) / Contract agreement(s).</p> <p>i) Bill of Lading (OR) ii) Commercial Invoice / Payment of Invoice of the OEM (OR) iii) Central Excise Gate Pass/Tax Invoice issued under relevant rules of Central Excise/Vat/GST.</p>		
A.3	The bidder shall confirm that the Rotary Slips will be tested and certified as per API 7K (Latest Edition).		
A.4	The bidder must keep API licenses along with authorization for API monogram valid till execution of purchase order and must confirm that the offered product will be supplied with API Monogram.		
A.5	In case renewal process of API license is in progress at the time of bidding, the manufacturer should furnish a letter from API to this effect that renewal of the license is under examination with API and is authorized to manufacture the items as per API license and to use API monogram till the renewal for license is issued. The bidder shall also submit an undertaking that delay in renewal of API certificate shall not affect the stipulated delivery schedule of the tender / purchase order.		
A.6	Bidder should categorically confirm in the technical bid a delivery schedule within eight (08) months, FOB Port of dispatch, after establishment of letter of credit (in case of foreign bidder) or for dispatch of the equipment within eight (08) months after receipt of formal order (in case of indigenous bidder) failing which their offer will be rejected.		
A.7	If the bidder is a manufacturer and have successfully supplied eighteen (18) numbers of Hand Slips for drill pipes of any sizes, twelve (12) numbers of Hand Slips for drill collars of any sizes and fourteen (14) numbers of Hand Slips for casings of any sizes to OIL in the last 05 (five) years as on original bid closing date either by themselves or through their sole selling agent / distributor / dealer / supply house and whose past performance has been satisfactory, the bidder need not		

	satisfy Clause A.2. In this situation the bidder shall have to indicate the Purchase Order (P.O.) No. of OIL in their technical bid.		
B.	IN CASE THE BIDDER IS NOT A MANUFACTURER: If the bidder is a sole selling agent / distributor / dealer / supply house of any manufacturer(s), then bidder must furnish the following documents along with the technical bid failing which the bids will be rejected:		
B.1	Authorization certificate from the manufacturer(s) (in original on manufacturer's letter head) should be submitted along with the technical bid. This certificate should be valid at the time of bidding and should remain valid during the entire execution period of the order.		
B.2	Undertaking from the manufacturer(s) (in original on manufacturer's letter head) guaranteeing supply of items to the bidder in the event of an order on the bidder. This certificate should be valid at the time of bidding and should remain valid during the entire execution period of the order.		
B.3	Warranty backup from the manufacturer(s) in original on manufacturer's letter head against the quality of the tendered item(s) as specified in the tender.		
B.4	Copies of API Spec 7K certificates of the OEM(s) of their quoted product in line with para A.1 above.		
B.5	Documentary evidence in respect of manufacturing and supply experience as specified under para A.2 & A.2.1, if applicable or A.7 from the concerned manufacturer(s) (having supplied such items either by manufacturer themselves or through their sole selling agent / distributor / dealer / supply house) along with the techno-commercial bid.		
B.6	Documentary evidence in respect of bidder's own supply experience of supplying minimum 50% quantity (to be rounded to next higher whole figure) against each of the tendered item, of same or higher capacity and same or higher sizes, for which the bidder has quoted to any E&P companies/Drilling Contractors/Drilling service providers in the last 5 (five) years as on original bid closing date of the tender. Documentary evidence in respect of supplying the above mentioned items should be submitted with the technical bid, in the form of copies of relevant		

signed Purchase Orders along with copies of any of the following documents in respect of satisfactory execution of each of those Purchase Orders failing which the bids will be rejected:

- (i) Signed and sealed Satisfactory supply / completion report (in original on user's letter head) (OR)
- (ii) Bill of Lading (OR)
- (iii) Consignee delivery receipt / challan (OR)
- (iv) Central Excise Gate Pass / Tax Invoice issued under relevant rules of Central Excise / Vat / GST (OR)
- (v) Commercial Invoice / Payment Invoice

Note:

I) The Purchase Order date need not be within 5 (five) years preceding original bid closing date of this tender. However, the execution of supply should be within 5 (five) years preceding original bid closing date of this tender.

II) Original Bid Closing Date shall be considered by OIL for evaluation of BRC Criteria in case of any extension of the original bid closing date.

III) Satisfactory supply / completion report should be issued on company's letterhead with signature and stamp. Originals to be produced for verification on demand of OIL.

IV) In case the bidder submits the same Purchase Order(s) and relevant documents for supplementing the supply experience for both itself and the OEM(s), then the following additional documents are also to be submitted for supplementing the execution of supply from the OEM to the bidder as indicated in the submitted Purchase Order (s) failing which the bid will be rejected:

- a) Copies of Purchase Order / Contract between the Bidder and the OEM and any of the following documents:

	<p>i) Commercial Invoice / Payment invoice of the OEM (OR)</p> <p>ii) Bill of Lading (OR)</p> <p>iii) Central Excise Gate Pass/Tax invoice issued under relevant rules of Central Excise /VAT/GST</p>		
B.7	<p>Bidder should categorically confirm in the technical bid a delivery schedule within eight (08) months, FOB Port of dispatch, after establishment of letter of credit (in case of foreign bidder) or for dispatch of the equipment within eight (08) months after receipt of formal order (in case of indigenous bidder) failing which their offer will be rejected.</p>		
B.8	<p>If the bidder is sole selling agent / distributor / dealer / supply house of any manufacturer(s) and have successfully supplied eighteen (18) numbers of Hand Slips for drill pipes of any sizes, twelve (12) numbers of Hand Slips for drill collars of any sizes and fourteen (14) numbers of Hand Slips for casings of any sizes to OIL in the last 05 (five) years as on original bid closing date and whose past performance has been satisfactory, the bidder need not satisfy Clause B.6. In this situation the bidder shall have to indicate the Purchase Order (P.O.) No. of OIL in their technical bid. However, this exemption shall be applicable only if the bidder has declared in the bid that they will be supplying the Rotary Slips from the same manufacturer(s) as per the last order supply.</p>		
B.9	<p>The sole selling agent / distributor / dealer / supply house of any Original Equipment manufacturers should quote for the supply of Rotary Slips from those manufacturers who also meet the criteria as mentioned at clauses A.3, A.4 & A.5 above. The bidder is required to submit documentary evidence in respect of the above from the concerned manufacturer along with the techno-commercial bid.</p>		